



Energy Star[®]

QUALIFIED DOWNLIGHTS



FOCAL POINT[®]

ID+ 2.5"

Fixture	Housing Options									Trim Options							
	Housing Series	Trim Type	Lumen Output	Color Temp.	Distribution	Voltage	Driver	Housing Type	Factory Options	Aperture	Trim Type	Lumen Output	Color Temp.	Distribution	Optic	Finish	Optional Flange Finish
ID+ 2.5" ADJUSTABLE	FLCS2	RO RT	500L	27K	SP	120	L11	T	CP	LCS2	RDO RDT	500L	27K	SP	SL	CD	BP
			700L	30K	NFL1	277	LD1	BH	700L			30K	NFL1	SP00	WD	WP	
			900L	35K	NFL2	UNV			900L			35K	NFL2	SP35	WH		
			1100L	40K	FL1				1100L			40K	FL1				
			1300L	927K	FL2				1300L			927K	FL2				
			1500L	930K	LS				1500L			930K	LS				
				935K								935K					
	940K						940K										
ID+ 2.5" X 2.5" ADJUSTABLE	FLCS22	SO ST	500L	27K	SP	120	L11	T	CP	LCS22	SDO SDT	500L	27K	SP	SL	CD	BP
			700L	30K	NFL1	277	LD1	BH	700L			30K	NFL1	SP00	WD	WP	
			900L	35K	NFL2	UNV			900L			35K	NFL2	SP35	WH		
			1100L	40K	FL1				1100L			40K	FL1				
			1300L	927K	FL2				1300L			927K	FL2				
			1500L	930K	FL3				1500L			930K	FL3				
				935K	WFL1							935K	WFL1				
				940K	WFL2							940K	WFL2				
					VWFL								VWFL				
					LS1								LS1				



Energy Star[®]

QUALIFIED DOWNLIGHTS



FOCAL POINT[®]

ID+ 3.5"

Fixture	Housing Options									Trim Options				
	Housing Series	Trim Type	Lumen Output	Color Temp.**	Distributon	Voltage	Driver	Housing Type	Factory Options	Aperture	Trim Type	Optic	Reflector Color	Flange Finish
ID+ 3.5" ADJUSTABLE	FLCS3	RO	700L	27K	SP	120	LD1	IC	BH	LCS3	RO	AA	CD	BK
		RT	900L	30K	SPA	277	T	CP	RT		AAS	WD	WH	
			1100L	35K	NFL			EMR				BK		
			1300L*	40K	FL							WH		
*1300L T rated housing only. **80CRI only.														
ID+ 3.5" X 3.5" ADJUSTABLE	FLCS33	SO	700L	27K	SP	120	LD1	IC	BH	LCS3	RO	AA	CD	BK
		ST	900L	30K	SPA	277	T	CP	RT		AAS	WD	WH	
			1100L*	35K	NFL			EMR				BK		
				40K	FL							WH		
*1100L T rated housing only. **80CRI only.														

Fixture	Housing Options								Trim Options							
	Housing Series	Trim Type	Color Options	Lumen Output	Voltage	Driver	Housing Type	Factory Options	Aperture	Trim Type	Lumen Output	Color Temp	Optic	Distribution	Reflector Color	Optional Flange Finish
ID+ 3.5" DOWNLIGHT	FLC3D	RO	SW	700L	UNV	LD1	IC	BH	LC3	RO	700L	27K	DNT	NFL	CD	BP
		RDO		900L	120		T	CP		RDO	900L	30K	DNS	FL1	WD	WP
		RT		1100L	277					RT	1100L	35K	DSS	FL2	WH	
		RDT		1300L						RDT	1300L	40K		WFL		
				1500L							1500L	927K		VWFL*		
				1700L							1700L	930K		SWFL		
				1900L							1900L	935K				
				2100L							2100L	940K				
* VWFL not available in DNT/DNS.																
ID+ 3.5" X 3.5" DOWNLIGHT	FLC33D	SDO	SW	700L	UNV	LD1	IC	BH	LC33	SDO	700L	27K	DNT	NFL	CD	BP
		SDT		900L	120		T	CP		SDT	900L	30K	DNS	FL1	WD	WP
				1100L	277						1100L	35K	DSS	FL2	WH	
				1300L							1300L	40K		WFL		
				1500L							1500L	927K		VWFL*		
				1700L							1700L	930K		SWFL		
				1900L							1900L	935K				
				2100L							2100L	940K				
* VWFL not available in DNT/DNS.																

Fixture	Housing Options								Trim Options						
	Housing Series	Trim Type	Color Options	Lumen Output	Voltage	Driver	Housing Type	Factory Options	Aperture	Trim Type	Lumen Output	Color Temp	Optic	Reflector Color	Optional Flange Finish
ID+ 3.5" WALL WASH	FLC3W	RO	SW	700L	UNV	LD1	IC	BH	LC3	RO	700L	27K	WWT	CD	BP
		RT		900L	120		T	CP		RT	900L	30K	WWS	WH	WP
				1100L	277						1100L	35K			
				1300L							1300L	40K			
				1500L							1500L	927K			
				1700L							1700L	930K			
				1900L							1900L	935K			
		2100L						2100L	940K						
ID+ 3.5" X 3.5" WALL WASH	FLC33W	SDO	SW	700L	UNV	LD1	IC	BH	LC33	SDO	700L	35K	WWT	CD	BP
		SDT		900L	120		T	CP		SDT	900L	40K	WWS	WH	WP
				1100L	277						1100L				
				1300L							1300L				
				1500L							1500L				



Energy Star[®]

QUALIFIED DOWNLIGHTS



FOCAL POINT[®]

ID+ 4.5"

Fixture	Housing Options									Trim Options				
	Housing Series	Trim Type	Lumen Output	Color Temp.*	Distributor	Voltage	Driver	Housing Type	Factory Options	Aperture	Trim Type	Optic	Reflector Color	Flange Finish
ID+ 4.5" ADJUSTABLE	FLCS4	RO	1000L	27K	SP	120	L11	T	CP	LCS4	RDO RDT	SL SP00 SP30 SP40	CD WD WH	NP WP BP
		RT	1500L	30K	NFL	277		BH						
			2000L	35K	FL1	UNV								
			2500L	40K	FL2									
			3000L	927K	WFL									
			3500L	930K	VWFL									
			4000L	935K	LS									
		940K												
ID+ 4.5" X 4.5" ADJUSTABLE	FLCS44	SO	1000L	27K	SP	120	L11	T	CP	LCS44	SDO SDT	SL SP00 SP30 SP40	CD WD WH	NP WP BP
		ST	1500L	30K	NFL	277		BH						
			2000L	35K	FL1	UNV								
			2500L	40K	FL2									
			3000L	927K	WFL									
			3500L	930K	VWFL									
			4000L	935K	LS									
		940K												

Fixture	Housing Options							Trim Options							
	Housing Series	Trim Type	Output	Voltage	Driver	Housing Type	Factory Options	Aperture	Trim Type	Output	Color Temp.	Optic	Distribution	Color	Flange Finish
ID+ 4.5" DOWNLIGHT	FLC4D	RT	1000L	120V	L11	T	BH	LC4	RO RT	1000L	27K	DN	SP	CD	NP
		RO	1500L	277V		CP	1500L			30K	NFL		WH	BP	
			2000L			EM*	2000L			35K	FL1		WD*	WP	
			2500L				2500L			40K	FL2				
			3000L				3000L			927K	WFL				
										930K					
						935K									
						940K									
ID+ 4.5" X 4.5" DOWNLIGHT	FLC44D	SO	1000L	120V	L11	T	BH	LC44	SDO SDT	1000L	27K	DN	SP	CD	NP
		ST	1500L	277V		CP	1500L			30K	NFL		WH	WH	
			2000L			EM*	2000L			35K	FL1		WD*	BK	
			2500L				2500L			40K	FL2				
			3000L				3000L			927K	WFL				
										930K					
						935K									
						940K									

*80CRI only

*80CRI only



Energy Star[®]

QUALIFIED DOWNLIGHTS



FOCAL POINT[®]

ID+ 6"

Fixture	Housing Options							Trim Options						
	Housing Series	Trim Type	Output	Voltage	Driver	Housing Type	Factory Options	Aperture	Trim Type	Output	Color Temp.*	Optic	Color	Flange Finish
ID+ 6" DOWNLIGHT	FLC6D	RO RF	1000L	120	L11	T	BH CP EM	LC4	RD	1000L	30K	DN	CD WD BK WH	NP BP WP
			1500L	277						1500L	35K			
			2000L							2000L	40K			
			2500L							2500L				
			3000L							3000L				
			3000L							3000L				
*80CRI only														
ID+ 6" X 6" DOWNLIGHT	FLC66D	SO SF	1000L	120	L11	T	BH CP EM	LC66	SQ	1000L	30K	DN	CD WD BK WH	BK WH TS AL
			1500L	277						1500L	35K			
			2000L							2000L	40K			
			2500L							2500L				
			3000L							3000L				
			3000L							3000L				
*80CRI only														



Energy Star[®]

DIMMING COMPATIBILITY



FOCAL POINT[®]

All Energy Star-certified fixtures offer continuous dimming capability from either 100%-10% (LD1 option) or 100%-1% (L11 option). For more information on dimmer compatibility, please consult the driver manufacturers documentation.

Fixture	Housing Series	Lumen Range	Driver	Manufacturer Reference
ID+ 2.5"	FLCS2	All	L11	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
			LD1	
ID+ 2.5" X 2.5"	FLCS22	All	L11	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
			LD1	
ID+ 3.5"	FLCS3	All	LD1	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
	FLC3D			
	FLC3W			
ID+ 3.5" X 3.5"	FLCS33	All	LD1	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
	FLC33D			
	FLC33W			
ID+ 4.5"	FLCS4	1000L-2000L	L11	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
		2500L-4000L		Advance Xitanium 50W (XI050C140V054DSM1, XI050C140V054DSM5) Datasheet
	FLC4D	1000L-2000L	L11	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
		2500L-3000L		Advance Xitanium 50W (XI050C140V054DSM1, XI050C140V054DSM5) Datasheet
ID+ 4.5" X 4.5"	FLCS44	1000L-2000L	L11	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
		2500L-4000L		Advance Xitanium 50W (XI050C140V054DSM1, XI050C140V054DSM5) Datasheet
	FLC44D	1000L-2000L	L11	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
		2500L-3000L		Advance Xitanium 50W (XI050C140V054DSM1, XI050C140V054DSM5) Datasheet
ID+ 6"	FLC6D	1000L-2000L	L11	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
		2500L-3000L		Advance Xitanium 50W (XI050C140V054DSM1, XI050C140V054DSM5) Datasheet
ID+ 6" X 6"	FLC6D	1000L-2000L	L11	Advance Xitanium 25W (XI025C100V036DSM1, XI025C100V036DSM5) Datasheet
		2500L-3000L		Advance Xitanium 50W (XI050C140V054DSM1, XI050C140V054DSM5) Datasheet