


Blume® 3


DECORATIVE LED PENDANT




100's of customizable color combinations




Black trim detail




White trim detail



Palladium Silver trim detail



Solid shade detail from below





Blume 4 companions



Cylinder companions

DIMENSIONAL DATA (continued on page 4)



Canopy options



FEATURES

Nominal 12" diameter decorative PET felt shaded pendant.


Wide range of color options provides design flexibility and personalization for any project.

Optional Pinstripe detail may be specified in any of the available colors.


50° cut-off available with Solite lens for brightness control and visual comfort.

50° and 80° cut-off available for optimal visual comfort.

PERFORMANCE



28° Narrow Flood
Lumen Output: 1500lm
Total System Watts: 17W
Spacing Criterion: 0.50




89° Super Wide Flood
Lumen Output: 1500lm
Total System Watts: 17W
Spacing Criterion: 1.24

Photometric performance is measured in accordance with IESNA LM-79.
 Visit focalpointlights.com for complete photometric data.

Decorative Finishes



Finish Diagram



Canopy/Stem/Trim Paint Finishes



Cord Colors



PET Material

STANDARD COLORS



PREMIUM COLORS*




*Contact factory for lead time and pricing.


DIMENSIONAL DATA CONTINUED

SC - Shallow Canopy (Integral driver)


 Indicates Driver Location




PC - Power Canopy



DSC - Shallow Canopy with decorative J-box cover, Integral Driver




DPC - Power Canopy with decorative J-box cover



DIMENSIONAL DATA CONTINUED

4" Octogonal J-box required (By others)



LUMEN MULTIPLIER TABLE

Color Temperature & CRI			
Trim Type	Optic	Color Temperature	Multiplier
Round [RD]	ALL	2700K, 80+ CRI [27K]	0.93
		2700K, 90+ CRI [927K]	0.78
		3000K, 80+ CRI [30K]	0.97
		3000K, 90+ CRI [930K]	0.81
		3500K, 80+ CRI [35K]	1.00
		3500K, 90+ CRI [935K]	0.83
		4000K, 80+ CRI [40K]	1.01
		4000K, 90+ CRI [940K]	0.86
Optic & Distribution			
Trim Type	Optic	Distribution	Multiplier
Round [RD]	Tall Cone, 50° cut-off [DNT]	Narrow Flood (28") [NFL]	1.00
		Flood 1 (34") [FL1]	0.89
		Flood 2 (45") [FL2]	0.75
		Wide Flood (57") [WFL]	0.75
	Tall Cone, 50° cut-off with Solite Lens [DNTS]	Narrow Flood (28") [NFL]	0.97
	Super Short Cone, 80° cut-off [DSS]	Super Wide Flood (89") [SWFL]	0.74

Multiplier tables are provided to aid with estimation of lumen levels across options. Apply multipliers against ordered Lumen Output to estimate Delivered Lumens. Refer to IES files for most accurate photometric information.

How To Use Lumen Multipliers

Formula: (Lumen Output Value) x (Color Temperature & CRI) x (Optic & Distribution)

Example: DBL3-9-XX-XX-XX-XX-XX-XX-CD-XX-1000L-935K-1C-UNV-XX-DNT-FL1
(1000) x (0.83) x (0.87) ≈ 722 lm (estimated delivered lumens)