



Amica® 2 2x2

LED




lens detail




air return


DIMENSIONAL DATA



led options



Standard (1 LED Board)



High Efficiency (2 LED Boards)

FEATURES

Architectural recessed LED luminaire with classic lines to complement architecture.

Center ribbed diffuser masks LED brightness to create even illumination.


3.9" housing depth ideal for shallow plenum applications.

Access from below the ceiling for easy maintenance.

Connected Solutions: Integrates with wired and wireless building lighting control systems.

PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

PERFORMANCE



PRODUCT OVERVIEW

Lumen Output:	2000-5000lm
Wattage:	15-38
LPW:	124-136
SDCM:	3

High Performance
2000 Lumens (2000LH)

Delivered Lumens: 2000lm


Total System Watts: 15W

Photometric performance is measured in accordance with IESNA LM-79. Visit focalpointlights.com for complete photometric data.

fixture:

project:

MOUNTING INFORMATION



SPECIFICATIONS

LED System

LED module incorporates premium LEDs on a robust platform to achieve excellent thermal management. LEDs are placed to promote a uniform appearance. Available in 3000K, 3500K or 4000K with CRI>80, 3 SDCM. LED modules and drivers are replaceable from below.

Construction

One piece 24 Ga. steel reflector and housing. Bottom access 24 Ga. steel driver compartment. Top access plate for electrical connection. Positional brackets supplied as standard. Unit weight: 9 lbs.

Optic

24 Ga. steel reflectors finished in matte satin white powder coat. .084" thick frosted white acrylic diffuser with linear micro-prism pattern.

Electrical

Standard 120-277V driver includes 0-10V analog dimming. Power factor > .9. LD1 not Right Light as standard, consult factory. PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

Emergency

Emergency battery output—10 watts for 90 minutes. Maximum mounting height: 19.9ft Emergency Circuit with Connected Solutions (WSPC, NLT1, NXE1, WLXP) requires a UL924 compliant device, consult factory. PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

Labels

UL and cUL Listed. Suitable for Dry or Damp Locations, indoor use only.

Finish

Polyester powder coat applied over a multi-stage pre-treatment. Optional Anti-Microbial paint finish available.

Lumen Maintenance

Reported: L70 at > 60,000 hours Calculated: L70 at 145,000 hours
L80 at > 60,000 hours L80 at 91,000 hours
Derived from EPA TM-21 calculator. Based on typical conditions, consult factory for additional data.

Reliability

At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.

Warranty

LED system rated for operation in ambient environments up to 25°C. 5-year limited warranty.

PERFORMANCE CHART

Delivered Lumens		Tested System Watts	LPW	Lumen Multipliers		
				CCT	CRI	Multiplier
2000 Lumens	2000L	16	127	3000K	80	0.81
	2000LH	15	136		90	0.93
2500 Lumens	2500L	20	124	3500K	80	1.00
	2500LH	20	128		90	0.96
3000 Lumens	3000L	23	128	4000K	80	0.85
	3000LH	22	134		90	0.98
3500 Lumens	3500L	28	126			
	3500LH	27	134			
4000 Lumens	4000L	32	124			
	4000LH	31	132			
4500 Lumens	4500LH	35	131			
	5000LH	38	130			

Based on 3500K, 80 CRI. *Lumen output may vary +/- 8%. Actual wattage may vary +/- 5%

Focal Point LLC reserves the right to change specifications for product improvement without notification.

ORDERING		FAM2
Luminaire Series		
Amica 2	FAM2	
Nominal Size		22
2' x 2'	22	
Shielding		ACR
Ribbed Acrylic Diffuser	ACR	
Lumen Output		
Standard (1 LED Board)		
2000 Lumens	2000L	
2500 Lumens	2500L	
3000 Lumens	3000L	
3500 Lumens	3500L	
4000 Lumens	4000L	
High Efficiency (2 LED Boards)		
2000 Lumens	2000LH	
2500 Lumens	2500LH	
3000 Lumens	3000LH	
3500 Lumens	3500LH	
4000 Lumens	4000LH	
4500 Lumens	4500LH	
5000 Lumens	5000LH	
Color Temperature		
3000K, 80+ CRI or 90+ CRI	30K or 930K	
3500K, 80+ CRI or 90+ CRI	35K or 935K	
4000K, 80+ CRI or 90+ CRI	40K or 940K	
Circuit		1C
Single Circuit	1C	
Voltage		
120/277 UNV Volt	UNV	
347 Volt (LD1, WSPC only. Not available with EM.)	347	
Low Voltage	LV	
Control System & Dimming Level		
0-10V - 10% Dimming (Not Right Light as standard, consult factory)	LD1	
0-10V - 1% Dimming	L11	
Low Voltage, PoE compatible (No driver. Not available with EM, LV Voltage only.)	LVN	
Lutron Hi-Lume EcoSystem (LDE1) - 1% Dimming	LH1	
DALI - 1% Dimming	D11	
Step Dimming	SD5	
Wattstopper PLUS: Connected Light Module (0-10V standard. Consult factory for DALI.)	WSPC	
Acuity nLight® - 1% Dimming (Not available with CP.)	NLT1	
Current NX Enabled - 1% Dimming	NXE1	
WaveLinX Pro - 1% Dimming	WLXP	
Mounting		
Grid	G	
Drywall Frame Kit (Not available with WSPC, NXE1 or NLT1) (Cut out dimensions: Min: 24.25"/Max: 24.56")	F	
Surface Mount (Not available with WSPC, NXE1 or NLT1)	SM	
24" Aircraft Cable†	C24	
48" Aircraft Cable†	C48	
96" Aircraft Cable†	C96	
Factory Options		
Air Return (Overall height for luminaire with Air Return is 4.4")	AR	
Chicago Plenum (Not available with flex whip)	CP	
Emergency Battery†		
with Integral Test Switch	EM	
6' New York City Flex Whip (120V)†	FNY1	
6' New York City Flex Whip (277V)†	FNY2	
6' Flex Whip†	FW	
NSF Listed	NSF	
Finish		
Matte Satin White	WH	
Matte Satin White Anti-Microbial	WHA	


†Aircraft cable mounting not available with Flex Whip options.

QS 5/10* DAY Options in orange qualify for the Quickship program. 5-day up to 100 pieces, 10-day up to 300 pieces. Emergency Battery is 10-day only. Refer to Quickship Guide for complete details.

Focal Point provides broad flexibility through compatibility with a wide range of indoor lighting control systems. A variety of sensors, nodes, controllers, and drivers can be specified to scale the system and meet the needs of each application across both wired and wireless networks.

Features such as daylight harvesting, occupancy sensing, dimming, and switching help save energy, reduce costs, and enhance occupant comfort. All Connected Solutions luminaires require a compatible building control system.

Controls systems supplied by others. For performance data and additional control system details, please visit the connected solutions manufacturers websites.

Connected Solution	Ordering Code	Model #	Protocol	Compatible Networks (Not all compatible networks may be listed.)	Description	Occupancy & Daylight	Communication to Luminaire	Drivers (Primary drivers are listed in bold . To specify a particular driver please consult factory.)	Driver Type
 WATTSTOPPER®									
	WSPC	EN-ZBHA-CLM-DIM	ZigBee	Wattstopper PLUS	Node	Enabled†	Wireless	Advance by Signify	0-10V standard, consult factory for DALI
 COOPER Lighting Solutions									
	WLXP	OEM-WAA	WaveLinx Wireless	WaveLinx Pro Trellix	Sensor	Integrated*	Wireless (WaveLinx Pro Wireless Area Controller)	Advance by Signify	0-10V
 Current									
	NXE1	NXFM2-LV	NX	NX Distributed Intelligence	Controller	Enabled†	Wired	Optotronic by eldoLED	0-10V
 nLIGHT									
	NLT1	nEPS-60-IO	nLight	nLight	Controller	Enabled†	Wired	eldoLED ECOdrive, eldoLED SOLOdrive	0-10V

†Enabled: Luminaire supplied with a node/controller. Sensor to be provided by others.

*Integrated: Luminaire supplied with an installed sensor.