



Seem® 1

LED RECESSED



DIMENSIONAL DATA



FEATURES

Narrow extruded aluminum 1.5" recessed linear slot LED with Asymmetric, Batwing and Pop-Down lens options.

Individual units and continuous runs in 1" increments.


Frosted acrylic lens provides uninterrupted illumination, without pixels or shadows.

LED position and lens material optimized to provide the perfect blend of high performance and visual comfort.


Choice of output levels to meet a wide variety of application needs.

PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

DISTRIBUTIONS



Photometric performance is measured in accordance with IESNA LM-79.
Visit focalpointlights.com for complete photometric data.

DETAILS**SPECIFICATIONS****LED System**

Proprietary linear LED module incorporates premium LEDs on a robust platform to achieve excellent thermal management. LEDs are placed to promote a uniform appearance. Available in 3000K, 3500K or 4000K with both 80 and 90 CRI options. 3500K and 4000K with CRI>90 have a cyanosis observation index (COI) of 3.3 or less. LED modules and drivers are replaceable from below. Color accuracy <3 SDCM.

Construction

One piece extruded aluminum housing. 20 Ga. steel end caps. Housing for new construction applications. XFW acceptable for use with wood, consult factory for Type IC availability. 8' unit weight: 15lbs.

Optic

Reflectors fabricated of 22 Ga. steel finished in High Reflectance White powder coat. Extruded acrylic lens .07" thick with frosted finish, up to 8' continuous. 15-30" recommended distance from wall for Asymmetric Lens (AS).

Electrical

Luminaires are pre-wired with factory installed branch circuit wiring and over-molded quick connects. Standard 120-277V constant current driver includes 0-10V analog dimming. Power factor > .9. PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires. PoE runs require an independent PoE node and power feed for each luminaire section.

Emergency Battery

Emergency output - 10 watts for 90 minutes.

Labels

UL and cUL listed. Suitable for Dry or Damp Locations, indoor use only.

Finish

Polyester powder coat applied over a multi-stage pre-treatment.

Lumen Maintenance

Reported: L70 at >61,000 hours
L90 at >61,000 hours

Calculated: L70 at 470,000 hours
L90 at 115,000 hours

Derived from EPA TM-21 calculator. Based on typical conditions, consult factory for additional data.

Reliability

At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.

Warranty

LED system rated for operation in ambient environments up to 25°C. 5-year limited warranty.

4' PERFORMANCE CHART

See page 3.

ORDERING**Luminaire Series**

Seem 1 LED FSM1

Shielding**Asymmetric Lens**

AS

BW

FL

0.5" Pop-Down Lens PD05

(Not available with Tegular ceiling configurations)

Lumen Output

125 Lumens per foot
(4' minimum length,
Consult factory for Lutron, DALI)

250 Lumens per foot
(3' minimum length)

375 Lumens per foot

500 Lumens per foot

625 Lumens per foot

Color Temperature

3000K, 80+ CRI or 90+ CRI

3500K, 80+ CRI or 90+ CRI

4000K, 80+ CRI or 90+ CRI

Circuits & Zones

1 Circuit, non-emergency

Consult Ordering Guide on page 4 for
multiple circuiting and zoning options

Voltage

120/277 UNV Volt

347 Volt

(LD1 driver only)

Low Voltage

LV

Control System & Dimming Level

0-10V - 10% Dimming

0-10V - 1% Dimming

Low Voltage, PoE compatible

(No driver. Not available with EM or EC. LV Voltage only.)

Lutron Hi-Lume EcoSystem (LDE1) -

1% Dimming

DALI 1% Dimming

Ceiling Configuration

G1 or T1

G2 or T2

G3

G4 or T4

Tall 15/16" Lay-in or Tall 15/16" Tegular

(0.5" drop)

Tall 9/16" Lay-in or Tall 9/16" Tegular

9/16" Slot-tee Tegular

Tall 15/16" Lay-in or Tall 15/16" Tegular

Tall 15/16" Tegular for specialty ceilings

(0.5" drop)

Tall 9/16" Lay-in or Tall 9/16" Tegular

9/16" Tegular

No Flange for specialty ceilings

(Ex. slat, panel, cloud systems.)

Mud-in Trimless

Non-Drywall Hard Surface

Hard Surface, Wood

Factory Options

(See Ordering Guide on page 4 for
ordering details for DC, EC, EM & ECD.)

Chicago Plenum

DC

Daylight Circuit

EC

Emergency Circuit

Emergency Battery Pack[†]

Emergency Control Device[†]

([†]4' minimum length. 120/277 Volt only.)

6' New York City Flex Whip (120V)

6' New York City Flex Whip (277V)

6' Flex Whip

Finish

Matte White Housing

WH

Luminaire Length

Specify luminaire/row length

in 1" increments

(2' minimum, lengths are nominal 1" increments based
on T-centers. Housing length is 1" shorter than specified.

Leave blank for patterns. Smaller increments available,
consult factory.)

Pattern Options

(3' minimum length)

'L' pattern

'U' pattern

Rectangular pattern

(Consult factory for other pattern options)



Options in orange qualify for the Quickship program. 1000' total. Refer to
Quickship Guide for complete details including EM/EC options.


4' PERFORMANCE CHART

Lumen Output	Delivered Lumens	AS		BW		FL		PD05	
		Tested System Watts	Lumens Per Watt (LPW)	Tested System Watts	Lumens Per Watt (LPW)	Tested System Watts	Lumens Per Watt (LPW)	Tested System Watts	Lumens Per Watt (LPW)
125LF	500	5	95	5	93	6	89	6	87
250LF	1000	8	119	9	115	9	110	9	107
375LF	1500	11	131	12	125	13	119	13	116
500LF	2000	15	134	16	128	16	121	17	119
625LF	2500	18	135	19	129	20	122	21	119

Based on 3500K, 4' length. Lumen multipliers: Preferred Light = 0.65, 90 CRI = 0.87.
Delivered lumens may vary +/- 5%. Actual wattage may vary +/- 5%.

DIRECT ASYMMETRIC

Standard Application Example



No Flange for specialty ceilings NF
(Ex. slat, panel, cloud systems.)

Ordering Guide



Direct Only Linear Circuitry, Zones & Factory Options

HOW TO USE THIS GUIDE

Fill out the worksheet on the following page to specify your requirements for circuitry, zones, and factory options.


Refer to the run chart for standard run configurations, consult factory for custom configurations.

Complete the Totals / Ordering Codes at the bottom of the worksheet and add to your ordering logic on the cut sheet.

Submit the worksheet along with your order.

EXAMPLE	TOTAL RUN LENGTH: 32ft		JOB NAME: _____			Fixture Type: _____			
	HOUSING SECTION	SECTION LENGTH	SHARED ELECTRICAL FEED, NORMAL POWER			FACTORY OPTIONS			EM
			SWITCHING CIRCUIT	DIMMING ZONE	DAYLIGHT ZONE	DAYLIGHT CIRCUIT	EMERGENCY CIRCUIT	ECD	
	1	8	1C	1Z					1EM
	2	8	2C	2Z					
	3	8	2C	2Z					
	4	8				1DC			
	Totals / Ordering Codes		2C	2Z		1DC			1EM

ORDERING: FSM4L-FL-625LF-35K- **2C2Z** -UNV-LD1-G2- **1DC-1EM** -WH-32ft



KEY	
C = Switching Circuit Switched Hot / Shared Neutral	DC = Daylight Circuit Switched Hot / Separate Neutral
Z = Dimming Zone Dimming Control Wires	EC = Emergency Circuit Switched Hot / Separate Neutral
DL = Daylight Zone Daylight Dimming Control Wires	EM = Emergency Battery Unswitched Hot / Shared Neutral
	ECD = Emergency Control Device Unswitched Hot / Separate Neutral

DEFAULTS

- Zones and Factory Options illuminate entire sections from 4' to 8' in length.
- One shared or isolated circuit and zone required per housing section.
- Limit of one EM or ECD per housing section.
- Additional electrical feed required for applications greater than three shared circuits and zones.
- Each DC, EC and ECD require an additional electrical feed.
- ECD not available in the same housing section as EC.
- Longer lead times and additional pricing may apply for custom run configurations.

CUSTOM LENGTHS

- If partial illumination of emergency or daylight section is required, indicate in ordering guide and add "partial illumination" in Order Notes. Drawing required.
- Engineering validation required, longer lead times may apply.

Ordering Guide Worksheet

Linear Circuitry, Zones & Factory Options



WORKSHEET	TOTAL RUN LENGTH:		JOB NAME: _____			Fixture Type: _____		
	HOUSING SECTION	SECTION LENGTH	Shared Electrical Feed, Normal Power			FACTORY OPTIONS		
			Switching Circuit	Dimming Zone	Daylight Zone	Daylight Circuit	Emergency Circuit	ECD
	1							
2								
3								
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
Totals / Ordering Codes								

Combine to create Circuits & Zones ordering code Enter as individual Factory Options

RUN CHART

Run length (ft)	Housing Configuration Section Lengths	Run length (ft)	Housing Configuration Section Lengths	Run length (ft)	Housing Configuration Section Lengths	Run length (ft)	Housing Configuration Section Lengths
9	5 + 4	21	8 + 8 + 5	33	8 + 8 + 8 + 5 + 4	45	8 + 8 + 8 + 8 + 8 + 5
10	6 + 4	22	8 + 8 + 6	34	8 + 8 + 8 + 6 + 4	46	8 + 8 + 8 + 8 + 8 + 6
11	7 + 4	23	8 + 8 + 7	35	8 + 8 + 8 + 7 + 4	47	8 + 8 + 8 + 8 + 8 + 7
12	8 + 4	24	8 + 8 + 8	36	8 + 8 + 8 + 8 + 4	48	8 + 8 + 8 + 8 + 8 + 8
13	8 + 5	25	8 + 8 + 5 + 4	37	8 + 8 + 8 + 8 + 5		
14	8 + 6	26	8 + 8 + 6 + 4	38	8 + 8 + 8 + 8 + 6		
15	8 + 7	27	8 + 8 + 7 + 4	39	8 + 8 + 8 + 8 + 7		
16	8 + 8	28	8 + 8 + 8 + 4	40	8 + 8 + 8 + 8 + 8		
17	8 + 5 + 4	29	8 + 8 + 8 + 5	41	8 + 8 + 8 + 8 + 5 + 4		
18	8 + 6 + 4	30	8 + 8 + 8 + 6	42	8 + 8 + 8 + 8 + 6 + 4		
19	8 + 7 + 4	31	8 + 8 + 8 + 7	43	8 + 8 + 8 + 8 + 7 + 4		
20	8 + 8 + 4	32	8 + 8 + 8 + 8	44	8 + 8 + 8 + 8 + 8 + 4		

Standard run configurations, consult factory for custom configurations.