


Seem® 4

LED WALL MOUNT



0.5" pop-down lens




recessed companion



wall to ceiling companion



The Naturals collection - Light Oak shown




suspended companion



perimeter companion


DIMENSIONAL DATA




FEATURES

- Narrow extruded aluminum 4" wall mount direct LED.
- Individual units and continuous runs in 1' increments.
- Available in flush, asymmetric, asymmetric room fill, grazer or 0.5" pop-down lens.
- Choice of output levels to meet a wide variety of application needs.
- Tunable White: Supports human activity, well-being, and preferences with a light quality that evolves throughout the day.
- PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.
- Available with The Naturals, a series of finishes that exude biophilic beauty.

PERFORMANCE



MOUNTING INFORMATION



4' PERFORMANCE CHART

Lumen Output	Nominal Lumens	FL		AS		AF		GR	
		Tested System Watts	LPW						
275LF	1100	9.1	121	8.5	130	8.6	128	8	137
375LF	1500	11.7	129	10.8	138	11	137	10.8	139
625LF	2500	19.9	126	18.3	137	18.5	135	18.3	136
875LF	3500	27.9	125	25.9	135	26.2	133	25.7	136
1000LF	4000	32.2	124	29.8	134	30.2	132	29.7	135
1125LF	4500	36.6	123	33.9	133	34.4	131	33.8	133
1250LF	5000	41.2	121	38.1	131	38.6	129	37.9	132

Based on 3500K, 80 CRI, 4' lengths. Lumen multiplier: 90+ CRI = 0.87. Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%.

4' PERFORMANCE CHART - POP-DOWN

Lumen Output	Nominal Lumens	0.5"	
		Tested System Watts	LPW
275LF	1100	11	100
375LF	1500	14.7	102
625LF	2500	25	100
750LF	3000	30.3	99
875LF	3500	35.7	98
1000LF	4000	41.3	97

Based on 3500K, 80 CRI, 4' lengths. Lumen multiplier: 90+ CRI = 0.87. Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%.


STANDARD WHITE

Luminaire Series	FSM4LW
Seem 4 LED	FSM4LW
Shielding	
Asymmetric Lens	AS
Asymmetric Room Fill	AF
Flush Satin Lens	FL
Grazer	GR
0.5" Pop-Down Lens (1000LF max.)	PD05
Lumen Output	
275 Lumens per foot (Not available with Lutron Drivers.)	275LF
375 Lumens per foot (Not available with LH1 Drivers)	375LF
625 Lumens per foot (3' minimum with LH1 Drivers)	625LF
750 Lumens per foot (Pop-Down Lens only)	750LF
875 Lumens per foot	875LF
1000 Lumens per foot	1000LF
1125 Lumens per foot	1125LF
1250 Lumens per foot	1250LF
Color Temperature	
2700K, 80+ CRI or 90+ CRI	27K or 927K
3000K, 80+ CRI or 90+ CRI	30K or 930K
3500K, 80+ CRI or 90+ CRI	35K or 935K
4000K, 80+ CRI or 90+ CRI	40K or 940K
Circuits & Zones	
1 Circuit, non-emergency	1C
Consult Ordering Guide on page 3 for multiple circuiting and zoning options	_C_Z_DL
Voltage	
120/277 UNV Volt	UNV
Low Voltage	LV
Control System & Dimming Level	
0-10V - 10% Dimming	LD1
0-10V - 1% Dimming	L11
Low Voltage, PoE compatible (No driver. Not available with LM or EC, LV Voltage only)	LVN
Lutron Hi-Lume EcoSystem (LDE1) - 1% Dimming	LH1
DALI 1% Dimming	D11
Mounting	
Wall Mount	WM
Factory Options (See Ordering Guide on page 3 for ordering details for DC, EC, EM & ECD.)	
Daylight Circuit	_DC
Emergency Circuit	_EC
Emergency Battery Pack [†]	_EM
Emergency Control Device [†]	_ECD
[†] (4' minimum. 120/277 Volt only. EM or ECD not available at corners.)	
Finish (See finishes page for The Naturals options)	
Black	BK
Titanium Silver	TS
Matte White Housing	WH
Luminaire Length (Leave blank for patterns. Lengths are nominal)	
Specify luminaire/row length in 1' increments (2' minimum length. Smaller increments available. Consult factory for details.)	X'
Pattern Options (3' minimum length)	
'L' pattern	A' x B'
'U' pattern	A' x B' x C'
Rectangular pattern (Consult factory for other pattern options)	A' x B' R



Options in orange qualify for the Quickship program. Run lengths in 1' increments, 1000' total. Refer to Quickship Guide for complete details including EM/EC options.

MOUNTING INFORMATION



TW 4' PERFORMANCE CHART

Lumen Output	Nominal Lumens	Tested System Watts	FL
275LF	1100	10.8	102
375LF	1500	14.5	104
625LF	2500	24.9	100
875LF	3500	35.9	97
1000LF	4000	41.2	97
1125LF	4500	46.9	96

Based on 2700K, 90CRI, 4' lengths. Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%.

TW 4' PERFORMANCE CHART - POP-DOWN

Lumen Output	Nominal Lumens	0.5"	
		Tested System Watts	LPW
275LF	1100	13.1	84
375LF	1500	18.3	82
625LF	2500	31.7	79
750LF	3000	38.8	77

Based on 2700K, 90CRI, 4' lengths. Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%.

Lumen Multipliers

CRI	Multiplier
80+	1.16
90+	1.00

Wattage Multipliers

CCT	Multiplier
2700K	1.00
3000K	0.96
3500K	0.92
4000K	0.89
5000K	0.88
5700K	0.87



TUNABLE WHITE

Luminaire Series	Seem 4 LED	FSM4LW
Shielding	Flush Satin Lens	FL
	0.5" Pop-Down Lens (750LF max.)	PD05
Lumen Output	275 Lumens per foot (FL 3' min. with D1TW)	275LF
	375 Lumens per foot	375LF
	625 Lumens per foot	625LF
	750 Lumens per foot (Pop-Down Lens only)	750LF
	875 Lumens per foot	875LF
	1000 Lumens per foot	1000LF
	1125 Lumens per foot	1125LF
Color Temperature	Tunable White: 2700-6500K, 80+ CRI	2765T
	Tunable White: 2700-6500K, 90+ CRI	92765T
Circuits & Zones	1 Circuit, non-emergency	1C
	Consult Ordering Guide on page 3 for multiple circuiting and zoning options	_C_Z_DL
Voltage	120/277 UNV Volt	UNV
Control System & Dimming Level	DALI 1% Dimming	D1TW
	(Default driver offers DT6 control. It requires two addresses, one for intensity & one for CCT tuning. Consult factory for DT8. Extended lead time applies.)	
Mounting	Wall Mount	WM
Factory Options	(See page 4 for ordering details for DC, EC, EM & ECD.)	
	Daylight Circuit	_DC
	Emergency Circuit	_EC
	Emergency Battery Pack [†]	_EM
	Emergency Control Device [†]	_ECD
	[†] (Consult factory)	
Finish	(See finishes page for The Naturals options)	
	Black	BK
	Titanium Silver	TS
	Matte White Housing	WH
Luminaire Length	(2' minimum length. Smaller increments available. Consult factory for details. Lengths are nominal. Leave blank for patterns)	
	Specify luminaire/row length in 1' increments	X'
Pattern Options	(3' min. length. Consult factory for other pattern option.)	
	'L' pattern	A' x B'
	'U' pattern	A' x B' x C'
	Rectangular pattern	A' x B' R

Finishes



STANDARD FINISHES



WHITE WH BLACK BK TITANIUM SILVER TS

THE NATURALS (25% SCALE)



LIGHT OAK LOK GRAY ELM GRE CHESTNUT CHT WALNUT WLT WOVEN LINEN WLN

Ordering Guide



Direct Only Linear Circuitry, Zones & Factory Options

HOW TO USE THIS GUIDE

Fill out the worksheet on the following page to specify your requirements for circuitry, zones, and factory options.


Refer to the run chart for standard run configurations, consult factory for custom configurations.

Complete the Totals / Ordering Codes at the bottom of the worksheet and add to your ordering logic on the cut sheet.

Submit the worksheet along with your order.

TOTAL RUN LENGTH: <u>32ft</u>		JOB NAME: _____			FIXTURE TYPE: _____				
EXAMPLE	HOUSING SECTION	SECTION LENGTH	SHARED ELECTRICAL FEED, NORMAL POWER			FACTORY OPTIONS			
			SWITCHING CIRCUIT	DIMMING ZONE	DAYLIGHT ZONE	SEPARATE ELECTRICAL FEEDS			EM
						DAYLIGHT CIRCUIT	EMERGENCY CIRCUIT	ECD	
1	8	1C	1Z					1EM	
2	8	2C	2Z						
3	8	2C	2Z						
4	8				1DC				
Totals / Ordering Codes		2C	2Z		1DC			1EM	

ORDERING: FSM4L-FL-625LF-35K- **2C2Z** -UNV-LD1-G2- **1DC-1EM** -WH-32ft



KEY	
C = Switching Circuit Switched Hot / Shared Neutral	DC = Daylight Circuit Switched Hot / Separate Neutral
Z = Dimming Zone Dimming Control Wires	EC = Emergency Circuit Switched Hot / Separate Neutral
DL = Daylight Zone Daylight Dimming Control Wires	EM = Emergency Battery Unswitched Hot / Shared Neutral
	ECD = Emergency Control Device Unswitched Hot / Separate Neutral

DEFAULTS

- Zones and Factory Options illuminate entire sections from 4' to 8' in length.
- One shared or isolated circuit and zone required per housing section.
- Limit of one EM or ECD per housing section.
- Additional electrical feed required for applications greater than three shared circuits and zones.
- Each DC, EC and ECD require an additional electrical feed.
- ECD not available in the same housing section as EC.
- Longer lead times and additional pricing may apply for custom run configurations.

CUSTOM LENGTHS

- If partial illumination of emergency or daylight section is required, indicate in ordering guide and add "partial illumination" in Order Notes. Drawing required.
- Engineering validation required, longer lead times may apply.

Ordering Guide Worksheet

Linear Circuitry, Zones & Factory Options



FOCAL POINT®

TOTAL RUN LENGTH: _____		JOB NAME: _____			FIXTURE TYPE: _____			
HOUSING SECTION	SECTION LENGTH	SHARED ELECTRICAL FEED, NORMAL POWER			FACTORY OPTIONS			EM
		SWITCHING CIRCUIT	DIMMING ZONE	DAYLIGHT ZONE	SEPARATE ELECTRICAL FEEDS			
DAYLIGHT CIRCUIT	EMERGENCY CIRCUIT				ECD			
1								
2								
3								
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
Totals / Ordering Codes								

WORKSHEET

Combine to create Circuits & Zones ordering code

Enter as individual Factory Options

RUN CHART

Run length (ft)	Housing Configuration Section Lengths	Run length (ft)	Housing Configuration Section Lengths	Run length (ft)	Housing Configuration Section Lengths	Run length (ft)	Housing Configuration Section Lengths
9	5 + 4	21	8 + 8 + 5	33	8 + 8 + 8 + 5 + 4	45	8 + 8 + 8 + 8 + 8 + 5
10	6 + 4	22	8 + 8 + 6	34	8 + 8 + 8 + 6 + 4	46	8 + 8 + 8 + 8 + 8 + 6
11	7 + 4	23	8 + 8 + 7	35	8 + 8 + 8 + 7 + 4	47	8 + 8 + 8 + 8 + 8 + 7
12	8 + 4	24	8 + 8 + 8	36	8 + 8 + 8 + 8 + 4	48	8 + 8 + 8 + 8 + 8 + 8
13	8 + 5	25	8 + 8 + 5 + 4	37	8 + 8 + 8 + 8 + 5		
14	8 + 6	26	8 + 8 + 6 + 4	38	8 + 8 + 8 + 8 + 6		
15	8 + 7	27	8 + 8 + 7 + 4	39	8 + 8 + 8 + 8 + 7		
16	8 + 8	28	8 + 8 + 8 + 4	40	8 + 8 + 8 + 8 + 8		
17	8 + 5 + 4	29	8 + 8 + 8 + 5	41	8 + 8 + 8 + 8 + 5 + 4		
18	8 + 6 + 4	30	8 + 8 + 8 + 6	42	8 + 8 + 8 + 8 + 6 + 4		
19	8 + 7 + 4	31	8 + 8 + 8 + 7	43	8 + 8 + 8 + 8 + 7 + 4		
20	8 + 8 + 4	32	8 + 8 + 8 + 8	44	8 + 8 + 8 + 8 + 8 + 4		

Standard run configurations, consult factory for custom configurations.