

Skydome™

LED STEM/CABLE MOUNT



FOCAL POINT®



bay blue - gloss



fabulous fuschia - gloss




golf green - gloss



modest mushroom - gloss



titanium silver



matte black



cable mount canopy detail




surface mount companion



recessed companion

DIMENSIONAL DATA



FEATURES

Pendant mount LED round dome with acrylic diffuser.

Nominal 2', 3' or 4' diameter housings are available.

Shallow 4.5" deep housing maintains low profile.

Convex lens design ensures an evenly illuminated diffuser.

Skydome™ is a good choice for open public spaces such as airport concourses, large lobbies, reception areas, schools and meeting rooms.

PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

PERFORMANCE

4' Diameter
7000 Lumen Nominal Output
Delivered Lumens: 7000lm
Total System Watts: 77W

Photometric performance is measured in accordance with IESNA LM-79.
Visit focalpointlights.com for complete photometric data.

PRODUCT OVERVIEW

Lumen Output: 2000-17000lm

Wattage: 25-194W


LPW: 71-90

SDCM: 3

fixture:

project:

STEM MOUNTING INFORMATION



SPECIFICATIONS

LED System

LED module incorporates premium LEDs on a robust platform to achieve excellent thermal management. LEDs are placed to promote a uniform appearance. Available in 2700K, 3000K, 3500K or 4000K with CRI>80 or CRI>90. 3500K and 4000K with CRI>90 have a cyanosis observation index (COI) of 3.3 or less. LED modules and drivers are replaceable from below.

Construction

18 Ga. spun steel housing. 18 Ga. spun steel mounting pan. Housing available in 25.2", 36.12" or 48.2" diameter x 4.5"H. Housing secured to mounting pan by torsion springs. 12" minimum suspension. 2' unit weight: 23lbs, 3' unit weight: 50lbs, 4' unit weight: 72lbs.

Optic

20 Ga. steel reflector finished in High Reflectance White powder coat. Convex lens of .125" thick white acrylic is secured to housing and removed with torsion springs.

Electrical

Standard 120-277V driver includes 0-10V analog dimming. Power factor > .9. Optional EcoSystem™ driver from Lutron available. PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

Emergency Battery

Bodine BSL310-CAN. Emergency output—10 watts for 90 minutes.

Labels

UL and cUL Listed. Suitable for Dry or Damp Locations, indoor use only.

Finish

Polyester powder coat applied over a multi-stage pre-treatment.

Lumen Maintenance

Reported: L70 at >54,000 hours Calculated: L70 at 76,000 hours
(Derived from EPA TM-21 calculator. Based on typical conditions, consult factory for additional data.)

Reliability

At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.

Warranty

LED system rated for operation in ambient environments up to 25°C. 5 year limited warranty.

PERFORMANCE CHART

Nominal Size	Delivered Lumens	Tested System Watts	LPW
2'	2000	25	80
	3000	39	77
	4000	56	71
3'	4000	48	83
	5000	61	82
	7000	87	80
	9000	117	77
4'	7000	77	91
	9000	100	90
	11000	123	89
	14000	159	88
	17000	194	88

Based on 3500K, 80 CRI. Lumen multiplier: 90+ CRI = 0.87. Lumen output may vary +/- 8%. Actual wattage may vary +/- 5%

Focal Point LLC reserves the right to change specifications for product improvement without notification.

ORDERING

Luminaire Series		FSDL	
Skydome LED	FSDL		
Nominal Size			
2' Diameter	22		
3' Diameter	33		
4' Diameter	44		
Shielding			CX
Frosted Lens	CX		
Lumen Output			
2' Diameter			
2000 Lumen	2000L		
3000 Lumen	3000L		
4000 Lumen	4000L		
3' Diameter			
4000 Lumen	4000L		
5000 Lumen	5000L		
7000 Lumen	7000L		
9000 Lumen	9000L		
4' Diameter			
7000 Lumen	7000L		
9000 Lumen	9000L		
11,000 Lumen	11000L		
14,000 Lumen	14000L		
17,000 Lumen	17000L		
Color Temperature			
2700K, 80+ CRI or 90+ CRI	27K or 927K		
3000K, 80+ CRI or 90+ CRI	30K or 930K		
3500K, 80+ CRI or 90+ CRI	35K or 935K		
4000K, 80+ CRI or 90+ CRI	40K or 940K		
Circuit			1C
Single Circuit	1C		
Voltage			UNV
120/277 UNV Volt	UNV		
Low Voltage	LV		
Driver			
0-10V - 1% Dimming	L11		
0-10V - 10% Dimming	LD1		
Low Voltage, PoE compatible	LVN		
<small>(No driver. Not available with EM or EC. LV Voltage only)</small>			
Lutron Hi-Lume EcoSystem (LDE1) - 1% Dimming	LH1		
Mounting			
24" Aircraft Cable	C24		
48" Aircraft Cable	C48		
96" Aircraft Cable	C96		
12" Rigid Stem	S12		
18" Rigid Stem	S18		
24" Rigid Stem	S24		
36" Rigid Stem	S36		
48" Rigid Stem	S48		
<small>(White stems and canopies supplied standard. For non-white housings: to match stem and housing color, add M to ordering code (S12M). To match stem, canopy and housing color, add MC to ordering code (S12MC) (Consult factory for other lengths)</small>			
Factory Options			
Emergency Battery	EM		
Solid Top Cover Plate	TC		
<small>(Painted to match housing. Not available with EM.)</small>			
Finish			
Matte Satin White	WH		
Gloss White	HW		
Titanium Silver	TS		
Matte Black	BK		
Bay Blue - Gloss	BB		
Fabulous Fuschia - Gloss	FF		
Golf Green - Gloss	GG		
Modest Mushroom - Gloss	MM		