



# Amica™ 2 1x2

LED




lens detail




air return


## DIMENSIONAL DATA



### led options



Standard  
(1 LED Board)



High Efficiency  
(2 LED Boards)

## FEATURES

Architectural recessed LED luminaire with classic lines to complement architecture.

Center ribbed diffuser masks LED brightness to create even illumination.


3.9" housing depth ideal for shallow plenum applications.

Access from below the ceiling for easy maintenance.

Connected Solutions: Integrates with wired and wireless building control systems.

PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

## PERFORMANCE



High Performance  
2000 Lumens (2000LH)  
**Delivered Lumens: 2000lm**  
**Total System Watts: 16W**

### PRODUCT OVERVIEW


Lumen Output: 2000-5000lm  
Wattage: 16-40  
LPW: 124-133  
SDCM: 3

Photometric performance is measured in accordance with IESNA LM-79. Visit [focalpointlights.com](http://focalpointlights.com) for complete photometric data.

fixture:

project:

**MOUNTING INFORMATION**



**SPECIFICATIONS**

**LED System**

LED module incorporates premium LEDs on a robust platform to achieve excellent thermal management. LEDs are placed to promote a uniform appearance. Available in 3000K, 3500K or 4000K with CRI>80, 3 SDCM. LED modules and drivers are replaceable from below.

**Construction**

One piece 24 Ga. steel reflector and housing. Bottom access 24 Ga. steel driver compartment. Top access plate for electrical connection. Positional brackets supplied as standard. Unit weight: 6.6 lbs.

**Optic**

24 Ga. steel reflectors finished in matte satin white powder coat. .084" thick frosted white acrylic diffuser with linear micro-prism pattern.

**Electrical**

Standard 120-277V driver includes 0-10V analog dimming. Power factor > .9. LD1 not Right Light as standard, consult factory. PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

**Emergency**

Emergency battery output—10 watts for 90 minutes. Maximum mounting height: 19.9ft Emergency Circuit with Connected Solutions (DLM1, LMFS1, LMFSD, NLT1, ENL1, CLM1, NXE1, WLXP) requires a UL924 compliant device, consult factory.

**Labels**

UL and cUL Listed. Suitable for Dry or Damp Locations, indoor use only.

**Finish**

Polyester powder coat applied over a multi-stage pre-treatment. Optional Anti-Microbial paint finish available.

**Lumen Maintenance**

Reported: L70 at > 60,000 hours      Calculated: L70 at 145,000 hours  
L80 at > 60,000 hours      L80 at 91,000 hours  
(Derived from EPA TM-21 calculator. Based on typical conditions, consult factory for additional data.)

**Reliability**

At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.

**Warranty**

LED system rated for operation in ambient environments up to 25°C. 5 year limited warranty.

**PERFORMANCE CHART**

Delivered Lumens	Tested System Watts	LPW	Lumen Multipliers		
			CCT	CRI	Multiplier
2000 Lumens	2000L	16	3000K	80	0.81
	2000LH	16			
2500 Lumens	2500L	20	3500K	80	1.00
	2500LH	20			
3000 Lumens	3000L	23	4000K	80	0.85
	3000LH	22			
3500 Lumens	3500L	28		90	0.98
	3500LH	27			
4000 Lumens	4000L	32			
	4000LH	31			
4500 Lumens	4500LH	35			
	5000 Lumens	5000LH	40		

Based on 3500K, 80 CRI. \*Lumen output may vary +/- 8%. Actual wattage may vary +/- 3%  
Focal Point LLC reserves the right to change specifications for product improvement without notification.

**ORDERING**  
**Luminaire Series**

Amica 2 FAM2

**Nominal Size**

1' x 2' 12

**Shielding**

Ribbed Acrylic Diffuser ACR

**Lumen Output**

Standard

(1 LED Board)

2000 Lumens 2000L

2500 Lumens 2500L

3000 Lumens 3000L

3500 Lumens 3500L

4000 Lumens 4000L

**High Efficiency**

(2 LED Boards)

2000 Lumens 2000LH

2500 Lumens 2500LH

3000 Lumens 3000LH

3500 Lumens 3500LH

4000 Lumens 4000LH

4500 Lumens 4500LH

5000 Lumens 5000LH

**Color Temperature**

3000K, 80+ CRI or 90+ CRI 30K or 930K

3500K, 80+ CRI or 90+ CRI 35K or 935K

4000K, 80+ CRI or 90+ CRI 40K or 940K

**Circuit**

Single Circuit 1C

**Voltage**

120/277 UNV Volt UNV

347 Volt 347

(LD1, CLM1 only. Not available with EM.)

Low Voltage LV

**Control System & Dimming Level**

0-10V - 10% Dimming LD1

(Not Right Light as standard, consult factory)

0-10V - 1% Dimming L11

Low Voltage, PoE compatible LVN

(No driver. Not available with EM. LV Voltage only)

Lutron Hi-Lume EcoSystem (LDE1) LH1

1% Dimming

DALI - 1% Dimming D11

Step Dimming SD5

Wattstopper DLM - 1% Dimming DLM1

Wattstopper Fixture Sensor LMFS1

Low Density - 1% Dimming

Wattstopper Fixture Sensor LMFSD

High Density - 1% Dimming

Acuity nLight\* - 1% Dimming NLT1

(Not available with CP)

Enlighted Smart Sensor - 1% Dimming ENL1

Encelium CLM Connected Lighting Module - 1% Dimming CLM1

Current NX Enabled - 1% Dimming NXE1

WaveLinX Pro - 1% Dimming WLXP

**Mounting**

Grid G

Drywall Frame Kit F

(Not available with DLM1, CLM1, NXE1 or NLT1)

(Cut out dimensions: Min: 12.25"/Max: 12.56"

Min: 24.25"/Max: 24.56")

Surface Mount SM

(Not available with DLM1, CLM1, NXE1 or NLT1)

24" Aircraft Cable C24

48" Aircraft Cable C48

96" Aircraft Cable C96

**Factory Options**

Air Return AR

(Overall height for luminaire with Air Return is 4.4")

Chicago Plenum CP

(Not available with flex whip)

Emergency Battery EM

with Integral Test Switch

6' New York City Flex Whip (120V) FNY1

6' New York City Flex Whip (277V) FNY2

6' Flex Whip FW

**Finish**

Matte Satin White WH

Matte Satin White Anti-Microbial WHA



Options in orange qualify for the Quickship program. 5-day up to 100 pieces, 10-day up to 300 pieces. Refer to Quickship Guide for complete details.

Focal Point provides flexibility in meeting the needs of each project by integrating with several building lighting control systems. A variety of sensors, drivers and other components can be specified that allow the luminaires to communicate with wired and wireless networks. All zoning can be digitally reconfigured through the application software. Daylight harvesting, occupancy sensing, integration with HVAC systems, and individual controls enable the monitoring and modulating of light levels and temperature in order to save energy, reduce costs and maximize occupants' comfort. All Connected Solutions luminaires require a compatible building control system.†

Connected Solution	Ordering Code	Model #**	Protocol	Compatible Networks*	Occupancy & Daylight	Temperature Reporting	Communication to Luminaire	Drivers	
 WATTSTOPPER®		DLM1	LMFC-011	DLM	DLM	Enabled	No	Wired 	<b>Advance by Signify,</b> Optotronic by eldoLED
		LMFS1	LMFS-601 & LMFI-111	DLM Wireless	DLM	Enabled	No	Wireless	<b>Advance by Signify</b> Optotronic by eldoLED (Dexal)
	LMFSD	LMFS-601							
		WLXP	OEM-WAA	WaveLinx Wireless	WaveLinx Pro Trellix	Enabled	No	Wireless (WaveLinx Pro Wireless Area Controller)	<b>Advance by Signify</b>
		D11	Specified Driver	DALI	Crestron Züm Wireless & SpaceBuilder	Enabled	No	Wired	<b>eldoLED ECOdrive</b>
		L11		0-10V					<b>Advance by Signify</b>
		CLM1	ZBHA-CLM-DIM-ENC	ZigBee	Encelium X Light Management System	Enabled	No	Wireless	<b>Optotronic by eldoLED</b> Advance by Signify
		ENL1	SU-5E-IOT	Enlighted RF	Enlighted	Integrated	Yes	Wireless	<b>Advance by Signify</b>
		LH1	LDE1	EcoSystem	Quantum, Energi Savr Node, Energi TriPak	Enabled	No	Wired	<b>Lutron Hi-Lume</b>
		NLT1	nEPS-60-IO	nLight	nLight	Enabled	No	Wired 	<b>eldoLED ECOdrive,</b> eldoLED SOLOdrive
								Wireless 	
		NXE1	NXFM-LV	NX	NX Distributed Intelligence	Enabled	No	Wired 	<b>Optotronic by eldoLED</b>

\*Not all compatible networks may be listed. \*\*For performance data and additional control system details please visit the connected solutions manufacturer websites. Primary drivers are listed in **bold**. To specify a particular driver please consult factory. †Controls systems supplied by others.