



Aerion® 1x4

LED



standard diffuser



round accent strip



square accent strip



red insert




green insert




blue insert

DIMENSIONAL DATA



Overall height for luminaire with Air Return is 3.96"



2 LED boards

FEATURES

Architectural recessed LED luminaire.

Aerion's sweeping curves and contemporary lines complement architecture.


Aerion's center lamp chamber provides minimal contrast between the diffuser and side reflectors creating even illumination and comfort.

Aerion features a shallow 3.3" housing depth which flies under the radar of most plenum obstructions.

The lamp diffuser has been designed with an upper and lower track that accepts individual or combinations of accent strips.

PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

PERFORMANCE



PRODUCT OVERVIEW

Lumen Output: 2500-4000lm

Wattage: 23-40W

LPW: 100-109

SDCM: 3


Delivered Lumens: 3000lm

Total System Watts: 28W

Photometric performance is measured in accordance with IESNA LM-79. Visit focalpointlights.com for complete photometric data. Visit designlights.org/QPL for model specifics.


MOUNTING INFORMATION

grid
for lay-in grid, specify G1, G2 or G3.



g1
15/16"
g2
9/16"
g3
slot 9/16"

drywall frame kit
specify "DF" Drywall Frame Kit for drywall ceiling conditions.



Use tie-wire or screws to secure frame kit.

cut out dimensions:
1': Min: 12.25" Max: 12.563"
4': Min: 48.25" Max: 48.563"

SPECIFICATIONS

LED System

Proprietary linear LED module incorporates premium LEDs on a robust platform to achieve excellent thermal management. LEDs are placed to promote a uniform appearance. Available in 3000K, 3500K or 4000K with CRI>80, 3 SDCM. 0-10V dimming driver standard. LED modules are replaceable from below.

Construction

One piece 20 Ga. steel reflector and housing. 20 Ga. steel ends form finishing housing. Side access 20 Ga. steel driver compartment. Positional brackets supplied as standard. Unit weight: 16 lbs.

Optic

20 Ga. steel reflectors finished in matte satin white powder coat. .095" thick frosted white acrylic lamp diffusers with linear micro-prism pattern. Optional .020" thick acrylic accent strip available in round or square pattern.

Electrical

Standard 120-277V driver includes 0-10V analog dimming. Power factor > .9. Optional EcoSystem or forward phase dimming drivers from Lutron available. PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

Emergency Battery

Bodine BSL310-CAN. Emergency output—10 watts for 90 minutes.

Labels

UL and cUL Listed. Suitable for Dry or Damp Locations, indoor use only.

Finish

Polyester powder coat applied over a multi-stage pre-treatment. Optional Matte Satin White with anti-microbial coating provides 99.99% protection against a broad spectrum of micro-organisms.

Lumen Maintenance

Reported: L90 at >61,000 hours Calculated: L90 at 114,000 hours
Derived from EPA TM-21 calculator. Based on typical conditions, consult factory for additional data.

Reliability

At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.

Warranty

LED system rated for operation in ambient environments up to 25°C. 5-year limited warranty.

PERFORMANCE CHART

Delivered Lumens		Tested System Watts	LPW
2500 Lumens	2500L	23	109
3000 Lumens	3000L	28	107
3500 Lumens	3500L	34	103
4000 Lumens	4000L	40	100

Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%

ORDERING

Luminaire Series	Aerion LED	FARL	FARL
Nominal Size	1' x 4'	14	14
Shielding	Acrylic Diffuser	AC	
	Acrylic Diffuser with Round Accent Strip	RA	
	Acrylic Diffuser with Square Accent Strip	SA	
Optional Color Inserts	(Leave blank for no color)		
	Red	R	
	Green	G	
	Blue	B	
Lumen Output	2500 Lumens	2500L	
	3000 Lumens	3000L	
	3500 Lumens	3500L	
	4000 Lumens	4000L	
Color Temperature	3000K	30K	
	3500K	35K	
	4000K	40K	
Circuit	Single Circuit	1C	1C
Voltage	120 Volt	120	
	277 Volt	277	
	UNV Volt	UNV	
(Cannot be specified with EM options)			
	Low Voltage	LV	
Control System & Dimming Level	0-10V - 1% Dimming	L11	
	0-10V - 10% Dimming	LD1	
	Low Voltage, PoE compatible	LVN	
(No driver. Not available with EM or EC. LV Voltage only)			
Lutron Hi-Lume EcoSystem (LDE1) -	1% Dimming	LH1	
Lutron Hi-Lume - Forward Phase -	1% Dimming	LTE	
	<small>(120 only)</small>		
	Step Dimming	SD5	
	DALI - 1% Dimming	D11	
	<small>(Consult factory)</small>		
Mounting	15/16" Grid	G1	
	9/16" Grid	G2	
	9/16" Slot Tee	G3	
	Drywall Frame Kit	F	
(Cut out dimensions: Min: 12.25"/Max: 12.563" Min: 48.25"/Max: 48.563")			
Factory Options	Air Return	AR	
	<small>(Overall height for luminaire with Air Return is 3.96")</small>		
	Chicago Plenum	CP	
	Emergency Battery Pack with Integral Test Switch	EM	
	6' New York City Flex Whip	FNY	
	6' Flex Whip	FW	
Finish	Matte White Housing	WH	
	Matte Satin White with Anti-Microbial Coating	WHA	