



# Verve™ IV


LED WALL MOUNT



linear companion



## DIMENSIONAL DATA



## FEATURES

Wall mounted direct/indirect LED with frosted lens.


Elegant wall-mount version of Focal Point's suspended Verve™ IV.

One-piece steel housing with 5" die-cast end caps

Verve IV is an excellent choice for commercial and educational facilities.

PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.


## PERFORMANCE



fixture:

project:

### SUSPENSION INFORMATION



### SPECIFICATIONS

#### LED Systems

Linear LED module incorporates premium LEDs on a robust platform to achieve excellent thermal management. Available in 3000K, 3500K, 4000K with CRI>80, 3SDCM. Contact factory for additional color temperature and CRI options. LED boards and drivers are replaceable.

#### Construction

One-piece 20 Ga. steel housing. Die-cast 5" end cap standard. For row installation, internal brackets form hairline joint. Standard lengths are available in 4' and 8'. All luminaires are provided with mounting brackets. 4' unit weight: 20 lbs., 8' unit weight: 30 lbs.

#### Optic

Reflector fabricated of 22 Ga. steel finished in high reflectance matte white. 24 Ga. steel beam softening filter finished in matte white powder coat. .010" thick acrylic lens.

#### Electrical

Luminaires are pre-wired with factory installed branch circuit wiring and over-molded quick connects. Standard 120-277V constant current driver includes 0-10V analog dimming. Power factor > .9. PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires. PoE runs require an independent PoE node and power feed for each luminaire section.

#### Emergency

Bodine BSL310LP. Emergency output—10 watts for 90 minutes. Maximum mounting height: 9.75ft.

#### Labels

UL and cUL listed. Suitable for Dry or Damp Locations, indoor use only.

#### Finish

Polyester powder coat applied over a multi-stage pre-treatment. Mounting arm and brackets finished to match housing.

#### Lumen Maintenance

Reported: L70 at >60,000 hours                      Calculated: L70 at 162,000 hours  
 L80 at >60,000 hours                                L80 at 102,000 hours  
 Derived from EPA TM-21 calculator. Based on typical conditions, consult factory for additional data.

#### Reliability

At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.

#### Warranty

LED system rated for operation in ambient environments up to 25°C. 5 year limited warranty.

### 4' PERFORMANCE CHART

Lumens Per Foot	Delivered Lumens	System Watts	LPW
625LF	2500	21	119
750LF	3000	25	120
875LF	3500	30	117

Based on 3500K. Color Temperature multipliers: 3000K - 1.035, 4000K - 0.975.\*Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%

### ORDERING

<b>Fixture Series</b>	Verve IV LED	<b>FV4LW</b>
<b>Shielding</b>	Frosted Lens	<b>FL</b>
<b>Lumen Output</b>	625 Lumens per foot	625LF
	750 Lumens per foot	750LF
	875 Lumens per foot	875LF
<b>Color Temperature</b>	3000K	30K
	3500K	35K
	4000K	40K
<b>Circuits</b>	Single Circuit	<b>1C</b>
<b>Voltage</b>	120/277 UNV Volt	UNV
	347 Volt	347
	(LD1 only)	
<b>Low Voltage</b>	LV	
<b>Control System &amp; Dimming Level</b>	0-10V - 1% Dimming	L11
	0-10V - 10% Dimming	LD1
	Low Voltage, PoE compatible	LVN
	(No driver. Not available with EM or EC. LV Voltage only)	
<b>Lutron Hi-Lume EcoSystem (LDE1) -</b>	1% Dimming	LH1
	DALI - 1% Dimming	D11
	Step Dimming	SD5
	(875LF only)	
<b>Mounting</b>	Wall Mount	<b>WM</b>
<b>Factory Options</b>	Emergency Battery	EM
	(120/277V only)	
	Emergency Circuit	EC
	Dust Cover	DST
<b>Finish</b>	Titanium Silver	TS
	Matte Satin White	WH
<b>Fixture Run Length</b>	4'	4'
	8'	8'
	12' (8'+4')	12'
	16' (8'+8')	16'
	20' (8'+4'+8')	20'
	24' (8'+8'+8')	24'