



Seem[®] 2


LED WALL TO CEILING CORNER



recessed



wall mount companion




suspended companion



perimeter companion

DIMENSIONAL DATA



FEATURES

Narrow extruded aluminum 2.5" aperture recessed slot LED that transitions from wall to ceiling.

Clean and minimal trimless drywall mounting.


Frosted acrylic lens provides uninterrupted illumination, without pixels or shadows.

LED position and lens material optimized to provide the perfect blend of high performance and visual comfort.

Choice of output levels to meet a wide variety of application needs.

Tunable White: Supports human activity, well-being, and preferences with a light quality that evolves throughout the day.


PERFORMANCE



fixture:

project:

TW 4' PERFORMANCE CHART

Shielding	Lumens per Foot	Delivered Lumens	Tested System Watts	LPW
Flush Lens 	125LF	500	7.25	69.0
	250LF	1000	12.90	80.9
	375LF	1500	18.55	85.7
	500LF	2000	24.21	87.9
	625LF	2500	29.86	89.2
	750LF	3000	34.34	92.9
	875LF	3500	39.71	93.5
	1000LF	4000	45.08	93.7

Based on 2700K, 80CRI, 4' lengths. Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%

Lumen Multiplier

Wattage Multipliers

CRI	Multiplier	CCT	Multiplier
80+	1.00	2700K	1.00
90+	0.89	3000K	0.92
		3500K	0.88
		4000K	0.86
		5000K	0.85
		5700K	0.87

TW

TUNABLE WHITE

Luminaire Series	Seem 2 LED	FSM2L	FSM2L
Shielding	Flush Lens	FL	FL
Lumen Output	125 Lumens per foot	125LF	
	250 Lumens per foot	250LF	
	375 Lumens per foot	375LF	
	500 Lumens per foot	500LF	
	625 Lumens per foot	625LF	
	750 Lumens per foot	750LF	
	875 Lumens per foot	875LF	
	1000 Lumens per foot	1000LF	
Color Temperature	Tunable White: 2700-6500K, 80+ CRI	2765T	
	Tunable White: 2700-6500K, 90+ CRI	92765T	
Circuit	Single Circuit	1C	1C
Voltage	UNV 120/277 Volt	UNV	
	347 volt (LD1 and L11 driver only)	347V	
Control System & Dimming Level	DALI - 1% Dimming*	D1TW	D1TW
<small>(Default driver offers DT6 control. It requires two addresses, one for intensity & one for CCT tuning. Consult factory for DT8. Extended lead time applies.)</small>			
Ceiling Configuration	Wall to Ceiling corner, 1/2" Drywall	CXF1	
	Wall to Ceiling corner, 5/8" Drywall	CXF2	
	Wall to Ceiling corner, any Drywall Thickness	CXFF	
	Wall to Ceiling corner, Hard Surface, Non-Drywall	CXFN	
	Wall to Ceiling corner, Wood	CXFW	
Factory Options	Chicago Plenum	CP	
	Emergency Circuit	_EC	
	Emergency Battery Pack	_EM	
<small>(4' minimum. See EM/EC Guide for default locations and ordering details.)</small>			
	6' New York City Flex Whip (120V)	FNY1	
	6' New York City Flex Whip (277V)	FNY2	
	6' Flex Whip	FW	
Finish	Matte White Housing	WH	WH
Luminaire Length	Specify luminaire/row length in 1' increments	X'CX'W	
<small>Example: 12C6W=12' in ceiling, 6' in wall</small>			