




# Seem® 1 Acoustic Trio


LED DIRECT




Alternate angle



Center detail




Unlit companion



Seem 1 Acoustic companion


## DIMENSIONAL DATA



## FEATURES

- Narrow, sound absorbing 1.5\" aperture 'Y' shaped acoustic pendant with direct distribution.
- Available in 4' and 6' diameters with 8\", 12\", and 16\" nominal housing heights.
- LED position and lens material optimized to provide the perfect blend of high performance and visual comfort.
- Engineered to maximize sound absorption and to create a statement as a stand-alone pendant, in a cluster or as part of a system when paired with Seem 1 Acoustic.
- AirCore™, patent pending, eco-friendly technology that maximizes sound absorption and reduces ecological impact.
- Wide range of color options provides design flexibility and personalization for any project.

## ACOUSTIC PERFORMANCE




All products were tested in multiple configured arrays. Total absorption will vary based on configuration. Please refer to ASTM C423 reports for more information.

fixture:

project:

## MOUNTING DETAILS



## SPECIFICATIONS

### Acoustic Material

Content	Housing material is 100% polyester containing up to 50% of recycled plastic bottles (PET felt) and is moisture resistant.  See page 3 for color offering. Acoustic material colors are subject to change without notice. For the most current color options, please visit <a href="http://focalpointlights.com/acousticsolutions">focalpointlights.com/acousticsolutions</a> . Lead times may vary depending on color.
Cleaning and Care	Remove dust and debris with a clean, soft, lint-free cloth or vacuum
PET Thickness	9mm
Surface Burning Characteristics	ASTM E84 Class A / CAN ULC S102 Flame Spread: 0 Smoke Development Index: 300

### Acoustic Performance

Acoustic testing is performed on all Focal Point acoustic products and varies based on installation and configuration. ASTM C423 test reports can be downloaded from [focalpointlights.com](http://focalpointlights.com).  
Contact [acoustic.solutions@focalpointlights.com](mailto:acoustic.solutions@focalpointlights.com) for technical questions.

Sabins	Sabins is a unit of sound absorption. It measures how well one square foot of material absorbs sound. Focal Point has averaged the Sabins per unit at four specific frequency bands representing the human speech range (250, 500, 1000, 2000 Hz) to determine the Sabins per product.  Sabins/unit varies based on configuration: Geo Y Configuration = 12.24 Sabins Staggered Hex Configuration = 12.07 Sabins
--------	--

### LED System

Proprietary linear LED module incorporates premium LEDs on a robust platform to achieve excellent thermal management. LEDs are placed to promote a uniform appearance. Available in 3000K, 3500K or 4000K with both 80 and 90 CRI options. LED drivers are replaceable from above. Color accuracy <3 SDCM.

### Weight

12" height, 4' diameter = 17.5lbs. 12" height, 6' diameter = 26.3lbs.

### Optic

Reflectors fabricated of 22 Ga. steel finished in Matte White powder coat. Extruded acrylic lens .05" thick with frosted finish, up to 8' continuous. 0.02" thick clear acrylic dust cover.

### Electrical

Luminaires are pre-wired with factory installed branch circuit wiring and over-molded quick connects. Standard 120-277V constant current driver includes 0-10V analog dimming. Power factor > .9. Power cord white as standard.

### Canopy

Polyester powder coat applied over a multi-stage pre-treatment. Canopy white as standard.

### Labels

ETL listed in accordance with UL standards. Suitable for Dry Locations, indoor use only.

### Lumen Maintenance

Reported: L70 at >61,000 hours  
L90 at >61,000 hours  
Calculated: L70 at 470,000 hours  
L90 at 115,000 hours

Derived from EPA TM-21 calculator. Based on typical conditions, consult factory for additional data.

### Reliability

At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.

### Warranty

LED system rated for operation in ambient environments up to 25°C. 5-year limited warranty.

## 4' PERFORMANCE CHART

See page 4

Focal Point LLC reserves the right to change specifications for product improvement without notification.

## ORDERING

Luminaire Series	ASM1TP
Seem 1 Acoustic Trio Direct	ASM1TP
<b>Nominal Size</b>	
4' Diameter	4
6' Diameter	6
<b>Shielding</b>	<b>RL</b>
Regress lens	RL
<b>Luminaire Height</b> (heights are nominal)	
8" nominal	8
12" nominal	12
16" nominal	16
<b>Direct Lumen Output</b>	
4' Diameter	
600 Lumens	600L
1200 Lumens	1200L
1800 Lumens	1800L
2400 Lumens	2400L
3000 Lumens	3000L
6' Diameter	
900 Lumens	900L
1800 Lumens	1800L
2700 Lumens	2700L
3600 Lumens	3600L
4500 Lumens	4500L
<b>Color Temperature</b>	
3000K, 80CRI or 90CRI	30K or 930K
3500K, 80CRI or 90CRI	35K or 935K
4000K, 80CRI or 90CRI	40K or 940K
<b>Circuit</b>	<b>1C</b>
Single Circuit	1C
<b>Voltage</b>	<b>UNV</b>
120/277 UNV Volt	UNV
<b>Control System &amp; Dimming Level</b>	
0-10V - 10% Dimming	LD1
0-10V - 1% Dimming	L11
Lutron Hi-Lume EcoSystem (LDE1) - 1% Dimming	LH1
DALI 1% Dimming	D11
<b>Mounting</b> (Mounting hang kits ship with order. Power cable is 18" longer than suspension length.)	
24" Cable Suspension	J24__
48" Cable Suspension	J48__
96" Cable Suspension	J96__
120" Cable Suspension	J120__
(Specify canopy color White (WH), Black (BK) or Titanium Silver (TS). Example: J24WH.) (Consult factory for sloped ceiling applications)	
<b>Factory Options</b>	
Black Cord	BKCD
<b>Acoustic Panel Color</b> See page 3 for color offering (Consult factory for multi-colored units)	


# Acoustic Material Colors



## STANDARD COLORS



## PREMIUM COLORS\*



\*Contact factory for lead time and pricing.

## Declare.

9mm PET Felt  
Focal Point, LLC

Final Assembly: Chicago, Illinois, USA  
Life Expectancy: 30 Year(s)  
End of Life Options: Salvageable/Reusable in its Entirety, Recyclable (100%)

### Ingredients:

Polyethylene terephthalate: PET; N, N'-Ethylene bisstearamide: Octadecanamide, N,N'-1,2-ethanediylbis-; Stearic Acid; Antioxidant 1076: Benzenepropanoic acid, 3,5-bis(1-(dimethylethyl)-4-hydroxy-octadecyl ester; Antioxidant KY-405: Benzenamine, 4-(1-methyl-1-phenylethyl)-N-(4-(1-methyl-1-phenylethyl)phenyl); Titanium Dioxide: Titanium dioxide

Living Building Challenge Criteria: Compliant

### I-13 Red List:


■ LBC Red List Free % Disclosed: 100% at 100ppm  
□ LBC Red List Approved VOC Content: Not Applicable  
□ Declared

I-10 Interior Performance: CDPH Standard Method v1.1-2010  
I-14 Responsible Sourcing: Not Applicable


FPL-0001  
EXP. 01 MAR 2024  
Original Issue Date: 2020

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY  
INTERNATIONAL LIVING FUTURE INSTITUTE™ [living-future.org/declare](http://living-future.org/declare)

## LIGHT REFLECTIVITY



4' DIAMETER PERFORMANCE CHART




Regress Lens

Photometric performance is measured in accordance with IESNA LM-79. Visit focalpointlights.com for complete photometric data.

Delivered Lumens	Tested System Watts	LPW
600	7.2	85
1200	12.5	98
1800	17.9	101
2400	24.2	102
3000	30.2	100

\*Based on 3500k, 80CRI, 4' lengths. Lumen multipliers: 90 CRI = 0.87. Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%.

6' DIAMETER PERFORMANCE CHART



Regress Lens

Photometric performance is measured in accordance with IESNA LM-79. Visit focalpointlights.com for complete photometric data.

Delivered Lumens	Tested System Watts	LPW
900	9.0	103
1800	15.9	114
2700	23.4	116
3600	31.7	114
4500	40.0	113

\*Based on 3500k, 80CRI, 4' lengths. Lumen multipliers: 90 CRI = 0.87. Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%.