

# TruTile® Shapes

ACOUSTIC WALL TILE



Scallop vertical rainbow fish pattern



Star vertical pattern



Open pattern detail



Closed pattern detail



The Naturals  
(Chestnut at 25% scale)

## SHAPES (8% scale)



## FEATURES

9mm thick, sound absorbing wall tiles available in 3 unique shapes that can be arranged to create a myriad of unique patterns.


Wide range of color options provides design flexibility and personalization for any project.

Available with The Naturals, a series of finishes that exude biophilic beauty.

Pair with Focal Point acoustic luminaires and unlit baffles to create a coordinated look within interior spaces.

See also TruTile Designs and TruTile Textures for more coordinated wall tile options.


## DIMENSIONAL DATA




fixture:

project:


PATTERN INSPIRATIONS




Gem vertical stack pattern




Gem horizontal stack pattern




Gem braid pattern



Scallop lantern pattern



Star vertical pattern



Star vertical/45° turn pattern

ORDERING

Series	AUTT
TruTile	AUTT
Size	22
2' x 2' panel	22
Shape	
Gem	GEM
Scallop	SCP
Star	STR
Design	SD
Solid	SD
Mounting	SM
Surface Mount by others	SM
(Construction glue direct to surface recommended)	
Acoustic Tile Color	
See page 3 for color offering	



Options in orange qualify for the Quickship program. Five color options. 10-day up to 200 pieces. Refer to Quickship Guide for complete details.

SPECIFICATIONS

Acoustic Material

Content	Material is 100% polyester containing up to 50% of recycled plastic bottles (PET felt) and is moisture resistant.  See Acoustic Materials page for color offering. Colors are subject to change without notice. For the most current color options, please visit <a href="http://focalpointlights.com/acousticsolutions">focalpointlights.com/acousticsolutions</a> . Lead times vary depending on color.
Cleaning and Care	Remove dust and debris with a clean, soft, lint-free cloth or vacuum
PET Thickness	9mm
Surface Burning Characteristics	ASTM E84 Class A / CAN ULC S102 Flame Spread: 0 Smoke Development Index: 300

Acoustic Performance

Acoustic testing is performed on all Focal Point acoustic products and varies based on installation and configuration. ASTM C423 test reports can be downloaded from [focalpointlights.com](http://focalpointlights.com). Contact [acoustic.solutions@focalpointlights.com](mailto:acoustic.solutions@focalpointlights.com) for technical questions.

NRC	Noise Reduction Coefficient (NRC) is the average of how absorptive a material is at various frequencies within the human speech frequency range. Two materials with the same rating may not perform the same in application. Typically, an NRC of 0 indicates perfect reflection, and an NRC of 1 is designated as perfect absorption. However, based on the testing methodology and depending upon the material's shape or surface area products can test at an NRC greater than 1.  NRC = 0.30
-----	--

Weight

1.8 lbs per tile. Ships up to (12) twelve per box = 25.25" x 25.25" x 5".

Reliability

At Focal Point, our products are designed to stand the test of time. Each product is engineered using superior components, manufactured with the utmost care and rigorously tested.

Warranty

1-year limited warranty.


# Acoustic Materials




## THE NATURALS (25% SCALE)



## STANDARD PET



## PREMIUM PET



**PET**  
Focal Point, LLC

Final Assembly: Chicago, Illinois, USA  
Life Expectancy: 30 Year(s)  
End of Life Options: Salvageable/Reusable in its Entirety, Recyclable (100%)

**Ingredients:**

Polyethylene terephthalate: PET; N, N'-Ethylene bisstearamide: Octadecanamide, N,N'-1,2-ethanediylbis-; Stearic Acid; Antioxidant 1076: Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, octadecyl ester; Antioxidant KY-405: Benzenamine, 4-(1-methyl-1-phenylethyl)-N-[4-(1-methyl-1-phenylethyl)phenyl]; Titanium Dioxide: Titanium dioxide

**Living Building Challenge Criteria:**

**I-13 Red List:**  
☒ LBC Red List Free  
☐ LBC Red List Approved  
☐ Declared

% Disclosed: 100% at 100ppm  
VOC Content: Not Applicable

**I-10 Interior Performance:** Not Compliant  
**I-14 Responsible Sourcing:** Not Applicable

FPL-0001  
EXP. 01 JUN 2026  
Original Issue Date: 2020

MANUFACTURED RESPONSIBLY FOR LABEL ACCURACY  
INTERNATIONAL LIVING FUTURE INSTITUTE™ [living-future.org/declare](http://living-future.org/declare)