


Seem® 4

LED WALL MOUNT




0.5" pop-down lens




recessed companion




wall to ceiling companion



The Naturals collection - Light Oak shown



suspended companion





perimeter companion


DIMENSIONAL DATA

Flush, Asymmetric, Room Fill, Grazer Lens

0.5" Pop-Down Lens



note: requires 4"x2" handy box.



↑ Power feed location in 8' start luminaire.

FEATURES

Narrow extruded aluminum 4" wall mount direct LED.

Individual units and continuous runs in 1' increments.

Available in flush, asymmetric, asymmetric room fill, grazer or 0.5" pop-down lens.


Choice of output levels to meet a wide variety of application needs.

Tunable White: Supports human activity, well-being, and preferences with a light quality that evolves throughout the day.

PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

Available with The Naturals, a series of finishes that exude biophilic beauty.


PERFORMANCE



fixture:

project:

MOUNTING INFORMATION



4' PERFORMANCE CHART

Lumen Output	Nominal Lumens	FL		AS		AF		GR	
		Tested System Watts	LPW	Tested System Watts	LPW	Tested System Watts	LPW	Tested System Watts	LPW
275LF	1100	9.1	121	8.5	130	8.6	128	8	137
375LF	1500	11.7	129	10.8	138	11	137	10.8	139
625LF	2500	19.9	126	18.3	137	18.5	135	18.3	136
875LF	3500	27.9	125	25.9	135	26.2	133	25.7	136
1000LF	4000	32.2	124	29.8	134	30.2	132	29.7	135
1125LF	4500	36.6	123	33.9	133	34.4	131	33.8	133
1250LF	5000	41.2	121	38.1	131	38.6	129	37.9	132

Based on 3500K, 80 CRI, 4' lengths. Lumen multiplier: 90+ CRI = 0.87. Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%.

4' PERFORMANCE CHART - POP-DOWN

Lumen Output	Nominal Lumens	0.5"	
		Tested System Watts	LPW
275LF	1100	11	100
375LF	1500	14.7	102
625LF	2500	25	100
750LF	3000	30.3	99
875LF	3500	35.7	98
1000LF	4000	41.3	97

Based on 3500K, 80 CRI, 4' lengths. Lumen multiplier: 90+ CRI = 0.87. Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%.

STANDARD WHITE

Luminaire Series		FSM4LW
Seem 4 LED		FSM4LW
Shielding		
Asymmetric Lens	AS	
Asymmetric Room Fill	AF	
Flush Satin Lens	FL	
Grazer	GR	
0.5" Pop-Down Lens (1000LF max.)	PD05	
Lumen Output		
275 Lumens per foot (Not available with Lutron Drivers.)	275LF	
375 Lumens per foot (Not available with LH1 Drivers)	375LF	
625 Lumens per foot (3' minimum with LH1 Drivers)	625LF	
750 Lumens per foot (Pop-Down Lens only)	750LF	
875 Lumens per foot	875LF	
1000 Lumens per foot	1000LF	
1125 Lumens per foot	1125LF	
1250 Lumens per foot	1250LF	
Color Temperature		
2700K, 80+ CRI or 90+ CRI	27K or 927K	
3000K, 80+ CRI or 90+ CRI	30K or 930K	
3500K, 80+ CRI or 90+ CRI	35K or 935K	
4000K, 80+ CRI or 90+ CRI	40K or 940K	
Circuits & Zones		
1 Circuit, non-emergency	1C	
Consult Ordering Guide on page 3 for multiple circuiting and zoning options	_C_Z_DL	
Voltage		
120/277 UNV Volt	UNV	
Low Voltage	LV	
Control System & Dimming Level		
0-10V - 10% Dimming	LD1	
0-10V - 1% Dimming	L11	
Low Voltage, PoE compatible (No driver. Not available with EM or EC. LV Voltage only.)	LVN	
Lutron Hi-Lume EcoSystem (LDE1) - 1% Dimming	LH1	
DALI 1% Dimming	D11	
Mounting		
Wall Mount	WM	
Factory Options		
(See Ordering Guide on page 3 for ordering details for DC, EC, EM & ECD.)		
Daylight Circuit	_DC	
Emergency Circuit	_EC	
Emergency Battery Pack†	_EM	
Emergency Control Device†	_ECD	
†(4' minimum. 120/277 Volt only. EM or ECD not available at corners.)		
Finish		
(See finishes page for The Naturals options)		
Black	BK	
Titanium Silver	TS	
Matte White Housing	WH	
Luminaire Length		
(Leave blank for patterns. Lengths are nominal)		
Specify luminaire/row length in 1' increments (2' minimum length. Smaller increments available. Consult factory for details.)	X'	
Pattern Options		
(3' minimum length)		
'L' pattern	A' x B'	
'U' pattern	A' x B' x C'	
Rectangular pattern	A' x B' R	
(Consult factory for other pattern options)		



Options in orange qualify for the Quickship program. Run lengths in 1' increments, 1000' total. Refer to Quickship Guide for complete details including EM/EC options.

SPECIFICATIONS

LED System

Proprietary linear LED module incorporates premium LEDs on a robust platform to achieve excellent thermal management. LEDs are placed to promote a uniform appearance. Available in 2700K, 3000K, 3500K or 4000K with CRI>80 or CRI>90, 3 SDCM or Tunable White (2700K-6500K), CRI>80, >90. 3500K and 4000K with CRI>90 have a cyanosis observation index (COI) of 3.3 or less. LED modules and drivers are replaceable from below.

Construction

One piece extruded aluminum housing. Die cast aluminum end caps. 2' unit weight: 10 lbs., 3' unit weight: 14 lbs., 4' unit weight: 18 lbs., 5' unit weight: 22 lbs.

Optic

Reflectors fabricated of 22 Ga. steel finished in High Reflectance White powder coat. Extruded acrylic lens .085" thick with satin finish, up to 8' continuous.

Electrical

Luminaires are pre-wired with factory installed branch circuit wiring and over-molded quick connects. Standard 120-277V constant current driver includes 0-10V analog dimming. Dimming range 100% to 10%. Power factor > .9. PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires. PoE runs require an independent PoE node and power feed for each luminaire section.

Emergency

Output - 10 watts for 90 minutes. Maximum mounting height: 19.2ft.

Labels

UL and cUL listed. Suitable for Dry or Damp Locations, indoor use only.

Finish

Polyester powder coat applied over a multi-stage pre-treatment. The Naturals: 100% low VOC vinyl.

Lumen Maintenance

Reported: L70 > 61,000 hours
L90 > 61,000 hours

Calculated: L70 at > 480,000 hours
L90 at > 128,000 hours

(Derived from EPA TM-21 calculator. Based on typical conditions, consult factory for additional data.)

Reliability


At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.

Warranty

LED system rated for operation in ambient environments up to 25°C. 5-year limited warranty.


DIRECT ASYMMETRIC

Standard Application Example



DIRECT ASYMMETRIC ROOM FILL

Standard Application Example




Asymmetric Room Fill Lens

The asymmetric room fill optic projects light into the space to evenly illuminate horizontal planes. It is ideal to light rooms and corridors from the perimeter, resulting in superior efficacy and uniformity on the floor.

DIRECT GRAZER

Standard Application Example



Grazer Lens

The grazer optic closely grazes walls, highlighting textures and architectural details. It is intended to provide even illumination and deliver maximum visual impact on the vertical surfaces.

Finishes



STANDARD FINISHES



THE NATURALS (25% SCALE)

