



Seem® 4

LED



0.5" pop-down lens



1.5" pop-down lens




recessed companion



wall to ceiling companion




wall mount companion





perimeter companion

DIMENSIONAL DATA



1.5" Pop-Down Lens

0.5" Pop-Down Lens



FEATURES

Narrow extruded aluminum 4" linear direct LED.

Individual units and continuous runs in 1' increments.

Available in flush, asymmetric, asymmetric room fill, batwing, 0.5" or 1.5" pop-down lens.

LED position and lens material optimized to provide the perfect blend of high performance and visual comfort.


Choice of output levels to meet a wide variety of application needs.

Tunable White: Supports human activity, well-being, and preferences with a light quality that evolves throughout the day.


Connected Solutions: Integrates with wired and wireless building lighting control systems.

PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

PERFORMANCE



DETAILS



TW 4' PERFORMANCE CHART

Lumen Output	Nominal Lumens	Tested System Watts	LPW	
			BW	FL
275LF	1100	13.30	87.3	83.2
375LF	1500	17.34	90.8	86.5
625LF	2500	27.84	94.0	89.5
875LF	3500	37.22	98.9	94.2
1000LF	4000	42.39	99.2	94.4
1125LF	4500	50.27	93.9	89.4

Based on 2700K, 80CRI, 4' lengths. Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%.

TW 4' PERFORMANCE CHART - POP-DOWN

Lumen Output	Nominal Lumens	0.5"		1.5"	
		Tested System Watts	LPW	Tested System Watts	LPW
275LF	1100	17.14	64.7	16.33	67.3
375LF	1500	22.79	66.5	21.58	70.0
625LF	2500	35.49	70.6	33.96	73.8
750LF	3000	42.39	70.8	40.28	74.5

Based on 2700K, 80CRI, 4' lengths. Lumen output may vary +/- 5%. Actual wattage may vary +/- 5%.

Lumen Multipliers

CRI	Multiplier
80+	1.00
90+	0.89

Wattage Multipliers

CCT	Multiplier
2700K	1.00
3000K	0.92
3500K	0.88
4000K	0.86
5000K	0.85
5700K	0.87
6500K	0.90



TUNABLE WHITE

Luminaire Series

Seem 4 LED FSM4LS

Shielding

Batwing Lens	BW
Flush Satin Lens	FL
0.5" Pop-Down Lens (750LF max.)	PD05
1.5" Pop-Down Lens (2' - 8' individual units only. 750LF max.)	PD15

Lumen Output

275 Lumens per foot (BW & FL 3' min. with DITW. PD05 & PD15 3' min. with LT1. FL & BW 4' min. with LT1.)	275LF
375 Lumens per foot (BW & FL 3' min. with LT1.)	375LF
625 Lumens per foot	625LF
750 Lumens per foot (Pop-Down Lens only)	750LF
875 Lumens per foot*	875LF
1000 Lumens per foot*	1000LF
1125 Lumens per foot*	1125LF

*(BW & FL only)

Color Temperature

Tunable White: 2700-6500K, 80+ CRI	2765T
Tunable White: 2700-6500K, 90+ CRI	92765T

Circuits & Zones

1 Circuit, non-emergency	1C
Consult Ordering Guide on page 4 for multiple circuiting and zoning options	_C_Z_DL

Voltage

120/277 UNV Volt	UNV
------------------	-----

Control System & Dimming Level

Lutron T-Series - 1% Dimming	LT1
DALI 1% Dimming	D1TW
(DT6 control. Requires two addresses, one for intensity & one for CCT tuning. Consult factory for DT8.)	
Acuity nLight - 1% Dimming**	NLT1
Enlighted Smart Sensor - 1% Dimming**	ENL1

** (Consult factory)

Mounting

24" Cable Suspension	C24__
48" Cable Suspension	C48__
96" Cable Suspension	C96__

(Specify canopy color White (WH), Black (BK) or Titanium Silver (TS). Example: C24WH.) (Specify one of the following in place of "C" J - for 2" canopies at non-feed locations. CS - for sloped ceiling applications.)

Surface Mount

(Not available with NLT1)

Factory Options

(See page 6 for ordering details for DC, EC, EM & ECD.)	
Black Cord	BKCD
Daylight Circuit	_DC
Emergency Circuit	_EC
Emergency Battery Pack†	_EM
Emergency Control Device†	_ECD

† (Consult factory)

Finish

Black	BK
Titanium Silver	TS
Matte White Housing	WH

Luminaire/Row Length

Specify in 1' increments X'

(Lengths are nominal, up to 8' individuals available. See Run Chart (page 8) for ordering codes. Smaller increments available, consult factory for details. Leave blank for patterns.)

Pattern Options

(3' min. length. Not available with Pop-Down lenses. Consult factory for other pattern options.)

Specify luminaire/row length in 1' increments	X'
'L' pattern	A' x B'
'U' pattern	A' x B' x C'
Rectangular pattern	A' x B'R

SPECIFICATIONS

LED System

Proprietary linear LED module incorporates premium LEDs on a robust platform to achieve excellent thermal management. LEDs are placed to promote a uniform appearance. Available in 2700K, 3000K, 3500K or 4000K with CRI>80 or CRI>90, 3 SDCM or Tunable White (2700K-6500K), CRI>80, >90. 3500K and 4000K with CRI>90 have a cyanosis observation index (COI) of 3.3 or less. LED modules and drivers are replaceable from below.

Construction

9-12' luminaires ship on 13' (157") pallets, forklift extensions of 72" are required to avoid damage. One piece extruded aluminum housing. Die cast aluminum end caps. 2' unit weight: 10 lbs., 3' unit weight: 14 lbs., 4' unit weight: 18 lbs., 5' unit weight: 22 lbs., 12' unit weight: 48 lbs.

Optic

Reflectors fabricated of 22 Ga. steel finished in High Reflectance White powder coat. Flush and Batwing extruded acrylic lens .085" thick with satin finish, up to 12' continuous. Pop-Down lenses extruded acrylic lens .06" thick with frosted finish.


Electrical

Luminaires are pre-wired with factory installed branch circuit wiring and over-molded quick connects. Standard 120-277V constant current driver includes 0-10V analog dimming. Dimming range 100% to 10%. Power factor > .9. PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires. PoE runs require an independent PoE node and power feed for each luminaire section.

Emergency

Emergency Battery output - 10 watts for 90 minutes. Maximum mounting height: 20.18ft. Emergency Circuit with Connected Solutions (DLM1, LMFS1, LMFS1, NLT1, ENL1, CLM1, NXE1, WLXP) shipped standard with leads to connect UL924 compliant device, by others.

MOUNTING INFORMATION



Labels

UL and cUL listed. Suitable for Dry or Damp Locations, indoor use only.

Finish

Polyester powder coat applied over a multi-stage pre-treatment. Canopy and cord white as standard.

Lumen Maintenance

Reported: L70 > 61,000 hours	Calculated: L70 at > 480,000 hours
L90 > 61,000 hours	L90 at > 128,000 hours

(Derived from EPA TM-21 calculator. Based on typical conditions, consult factory for additional data.)



Reliability

At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.



Warranty

LED system rated for operation in ambient environments up to 25°C. 5-year limited warranty.




















DIRECT ASYMMETRIC
Standard Application Example



DIRECT ASYMMETRIC ROOM FILL
Standard Application Example



Focal Point provides flexibility in meeting the needs of each project by integrating with several building lighting control systems. A variety of sensors, drivers and other components can be specified that allow the luminaires to communicate with wired and wireless networks. All zoning can be digitally reconfigured through the application software. Daylight harvesting, occupancy sensing, integration with HVAC systems, and individual controls enable the monitoring and modulating of light levels and temperature in order to save energy, reduce costs and maximize occupants' comfort. All Connected Solutions luminaires require a compatible building control system.†

Connected Solution		Ordering Code	Model #**	Protocol	Compatible Networks*	Occupancy & Daylight	Temperature Reporting	Communication to Luminaire	Drivers
 WATTSTOPPER®	 <small>Connections located under access panel.</small>	DLM1	LMFC-011	DLM	DLM	Enabled	No	Wired 	Advance by Signify, Optotronic by eldoLED
		LMFS1	LMFS-601 & LMFI-111	DLM Wireless	DLM	Enabled	No	Wireless	Advance by Signify
	LMFSD	LMFS-601	Optotronic by eldoLED (Dexal)						
		WLXP	OEM-WAA	WaveLinx Wireless	WaveLinx Pro Trellix	Enabled	No	Wireless (WaveLinx Pro Wireless Area Controller)	Advance by Signify
		D11	Specified Driver	DALI	Crestron Zūm Wireless & SpaceBuilder	Enabled	No	Wired	eldoLED ECOdrive
		L11		0-10V					Advance by Signify
		CLM1	ZBHA-CLM-DIM-ENC	ZigBee	Encelium X Light Management System	Enabled	No	Wireless	Optotronic by eldoLED Advance by Signify
		ENL1	SU-5E-IOT	Enlighted RF	Enlighted	Integrated	Yes	Wireless	Advance by Signify
		LH1	LDE1	EcoSystem	Quantum, Energi Savr Node, Energi TriPak	Enabled	No	Wired	Lutron Hi-Lume
	 <small>Connections located under access panel.</small>	NLT1	nEPS-60-IO	nLight	nLight	Enabled	No	Wired 	eldoLED ECOdrive, eldoLED SOLOdrive
		NXE1	NXFM-LV	NX	NX Distributed Intelligence	Enabled	No	Wired 	Optotronic by eldoLED
									

*Not all compatible networks may be listed. **For performance data and additional control system details please visit the connected solutions manufacturer websites. Primary drivers are listed in **bold**. To specify a particular driver please consult factory.
†Controls systems supplied by others.

Ordering Guide

Linear Circuitry, Zones & Factory Options

HOW TO USE THIS GUIDE

Fill out the worksheet on the following page to specify your requirements for circuitry, zones, and factory options.


Refer to the run chart for standard run configurations, consult factory for custom configurations.

Complete the Totals / Ordering Codes at the bottom of the worksheet and add to your ordering logic on the cut sheet.

Submit the worksheet along with your order.

EXAMPLE	TOTAL RUN LENGTH: 32ft		JOB NAME:			FIXTURE TYPE:		
	HOUSING SECTION	SECTION LENGTH	SHARED ELECTRICAL FEED, NORMAL POWER			FACTORY OPTIONS		
						SEPARATE ELECTRICAL FEEDS		
			SWITCHING CIRCUIT	DIMMING ZONE	DAYLIGHT ZONE	DAYLIGHT CIRCUIT	EMERGENCY CIRCUIT	ECD
								EM
	1	8	1C	1Z				
	2	8	2C	2Z				
	3	8	2C	2Z				
	4	8				1DC		
	Totals / Ordering Codes		2C	2Z		1DC		1EM

ORDERING: FSM4LS-FL-625LF-35K- 2C2Z -UNV-LD1-C24WH- 1DC-1EM -WH-32ft



KEY	
C = Switching Circuit Switched Hot / Shared Neutral	DC = Daylight Circuit Switched Hot / Separate Neutral
Z = Dimming Zone Dimming Control Wires	EC = Emergency Circuit Switched Hot / Separate Neutral
DL = Daylight Zone Daylight Dimming Control Wires	EM = Emergency Battery Unswitched Hot / Shared Neutral
	ECD = Emergency Control Device Unswitched Hot / Separate Neutral

DEFAULTS

- Zones and Factory Options illuminate entire sections from 4' to 8' in length.
- One shared or isolated circuit and zone required per housing section.
- Limit of one EM or ECD per housing section.
- Additional electrical feed required for applications greater than three shared circuits and zones.
- Each DC, EC and ECD require an additional electrical feed.
- ECD not available in the same housing section as EC.
- Longer lead times and additional pricing may apply for custom run configurations.

CUSTOM LENGTHS

- If partial illumination of emergency or daylight section is required, indicate in ordering guide and add "partial illumination" in Order Notes. Drawing required.
- Engineering validation required, longer lead times may apply.

Ordering Guide Worksheet

Linear Circuitry, Zones & Factory Options

WORKSHEET

TOTAL RUN LENGTH: JOB NAME: FIXTURE TYPE:

HOUSING SECTION	SECTION LENGTH	SHARED ELECTRICAL FEED, NORMAL POWER			FACTORY OPTIONS			
		SWITCHING CIRCUIT	DIMMING ZONE	DAYLIGHT ZONE	SEPARATE ELECTRICAL FEEDS			EM
					DAYLIGHT CIRCUIT	EMERGENCY CIRCUIT	ECD	
1								
2								
3								
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
Totals / Ordering Codes								

Combine to create Circuits & Zones ordering code

Enter as individual Factory Options

RUN CHART

Run Length (ft)	Housing Configuration Section Lengths	Ordering Code	Run Length (ft)	Housing Configuration Section Lengths	Ordering Code	Run Length (ft)	Housing Configuration Section Lengths	Ordering Code
9	5 + 4	9	19	8 + 7 + 4	19	35	8 + 8 + 8 + 7 + 4	35
	9	9(IND)	20	8 + 8 + 4	20	36	8 + 8 + 8 + 8 + 4	36
10	6 + 4	10	21	8 + 8 + 5	21	37	8 + 8 + 8 + 8 + 5	37
	5 + 5	10(5+5)	22	8 + 8 + 6	22	38	8 + 8 + 8 + 8 + 6	38
	10	10(IND)	23	8 + 8 + 7	23	39	8 + 8 + 8 + 8 + 7	39
11	7 + 4	11	24	8 + 8 + 8	24	40	8 + 8 + 8 + 8 + 8	40
	11	11(IND)	25	8 + 8 + 5 + 4	25	41	8 + 8 + 8 + 8 + 5 + 4	41
12	8 + 4	12	26	8 + 8 + 6 + 4	26	42	8 + 8 + 8 + 8 + 6 + 4	42
	6 + 6	12(6+6)	27	8 + 8 + 7 + 4	27	43	8 + 8 + 8 + 8 + 7 + 4	43
	12	12(IND)	28	8 + 8 + 8 + 4	28	44	8 + 8 + 8 + 8 + 8 + 4	44
13	8 + 5	13	29	8 + 8 + 8 + 5	29	45	8 + 8 + 8 + 8 + 8 + 5	45
14	8 + 6	14	30	8 + 8 + 8 + 6	30	46	8 + 8 + 8 + 8 + 8 + 6	46
15	8 + 7	15	31	8 + 8 + 8 + 7	31	47	8 + 8 + 8 + 8 + 8 + 7	47
16	8 + 8	16	32	8 + 8 + 8 + 8	32	48	8 + 8 + 8 + 8 + 8 + 8	48
17	8 + 5 + 4	17	33	8 + 8 + 8 + 5 + 4	33			
18	8 + 6 + 4	18	34	8 + 8 + 8 + 6 + 4	34			

Standard run configurations, consult factory for custom configurations.