



# DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

## RECESSED

Fixture	Luminaire Series	Nominal Size	Shielding	Lumen Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Options	Finish
AERION LED	FARL	14	AC	2500L	30K	1C	120	L11	G1	AR, CP, EM,	WH
			RA*	3000L	35K		277	LD1	G2	FNY, FW	WHA
			SA*	3500L	40K		UNV	G3			
				4000L				F		*RA & SA not DLC with 4000L	
		22	AC	2000L	30K	1C	120	L11	G1	AR, CP, EM,	WH
				2500LH	35K		277	LD1	G2	FNY, FW	WHA
				3000LH	40K		UNV	G3			
				3500LH				F			
		24	AC	4000L	30K	1C	120	L11	G1	AR, CP, EM,	WH
			RA*	4000LH	35K		277	LD1	G2	FNY, FW	WHA
			SA*	4500L	40K		UNV	G3			
				4500LH				F			
			5000L								
			5000LH								
			5500L								
	5500LH										
	6000LH						*RA & SA not DLC with 5000L or 5500L				
AMICA 2	FAM2	22	ACR	2500L <sup>†</sup>	30K	1C	UNV	LD1	G	AR	WH
				2500LH	35K		F	CP			
				3000L <sup>†</sup>	40K		SM	EM			
				3000LH			C24	FNY1			
				3500L <sup>†</sup>			C48	FNY2			
				3500LH			C96	FW			
				4000L <sup>†</sup>							
				4000LH							
		24	ACR	4000L	30K	1C	UNV	LD1	G	AR	WH
				4000LH	35K		F	CP			
				4500L	40K		SM	EM			
				4500LH			C24	FNY1			
		5000L		C48	FNY2						
		5000LH		C96	FW						
		5500L									
		5500LH									
		6000L									
		6000LH									
AMICA LED	FAML	22	ACR	2000L	30K	1C	120	L11	G1	AR, CP, EM,	WH
				2500LH	35K		277	LD1	G2	FNY, FW	WHA
				3000LH	40K		UNV	G3			
				3500LH				F			
		24	ACR	4000L	30K	1C	120	L11	G1	AR, CP, EM,	WH
				4000LH	35K		277	LD1	G2	FNY, FW	WHA
				4500L	40K		UNV	G3			
				4500LH				F			
		5000L									
		5000LH									
		5500L									
		5500LH									
	6000LH										

Amica 2 versions listed are DLC Premium unless otherwise indicated. Visit [designlights.org/QPL](http://designlights.org/QPL) for model specifics.



# DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

## RECESSED continued

Fixture	Luminaire Series	Nominal Size	Shielding	Lumen Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Options	Finish							
EQUATION 2	FEQ2	14	AC	2000L	30K	1C	UNV	LD1	C24	AR	WH							
				2500L	35K			L11	C48	CP								
				3000L	40K				C96	EM								
				3500L					F	FNY1								
				4000L					G	FNY2								
				4500L					ST	FW								
				5000L					SM									
		22	AC	2000	30K	1C	UNV	LD1	C24	AR	WH							
				2500*	35K			L11	C48	CP								
				3000*	40K				C96	EM								
				2000LH					F	FNY1								
				2500LH					G	FNY2								
				3000LH					ST	FW								
				3500LH					SM									
				4000LH														
				4500LH														
				5000LH														
				*LD1 driver only														
				24	AC			4000L	30K	1C		UNV	LD1	C24	AR	WH		
								4500L	35K				L11	C48	CP			
		5000L	40K				C96	EM										
		5500L					F	FNY1										
		4000LH					G	FNY2										
		4500LH					ST	FW										
		5000LH					SM											
		5500LH																
		6000LH																
		6500LH																
		7000LH																
		8000LH																
8500LH																		
FACETTA	FCT	22	FL			2000L	27K	1C	UNV		L11		F	CP, EM, FNY1, FNY2, FW	WH			
				2500L	30K	LD1	G											
				3000L	35K		ST											
				3500L	40K													
				4000L														
VEER LED	FVRL	24	ACF	4000L	30K	1C	120	L11	F	AR, CP, EM, FNY, FW	WH							
			ACG	4000LH	35K			LD1	G									
			ACR	4500LH	40K				UNV			ST						
				5000LH					SM									
				5500LH														
				6000LH														
ZEPHYR	FZR	14	FL	2000L	27K	1C	UNV	L11	F	CP, EM, FNY1, FNY2, FW	WH							
					30K			LD1	G									
					35K				ST									
					40K													
		22	FL	2000L	27K	1C	UNV	L11	F	CP, EM, FNY1, FNY2, FW	WH							
				2500L	30K			LD1	G									
				3000L	35K				ST									
				3500L	40K													
				4000L														



# DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

## LINEAR

Fixture	Luminaire Series	Shielding	Nominal Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Factory Options	Finish	Length
SEEM 4 LED SUSPENDED / WALL MOUNT	FSM4LS	FL	375LF	30K	1C	UNV	LD1	C24, C48, C96	EC, EM	TS	Individual units 4-8' and runs comprised of 4-8' units
			625LF	35K			L11				
	FSM4LW			40K				WM			
TWELVE LED	FTWLS	AC	750LF	30K*	1C	UNV	LD1	J12	DC, EC, EM	TS	4'
		MG	875LF	35K			J24	WH		8'	
			1000LF	40K			J48			12' (8' + 4')	
			1125LF				J96			16' (8' + 8')	
			1250LF				S__			20' (8' + 4' + 8') 24' (8' + 8' + 8')	

\*30K not DLC with 875LF, 1000LF or 1250LF

Fixture	Luminaire Series	Shielding	Nominal Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Suspension & Power Feed	Factory Options	Finish	Length	Run Configuration†
NERA	FNRS	FL60	500LF	30K	1C	UNV	LD1	G	CLV24	CSS	PS	4'	C4
		FL70	625LF	35K			HS	CLV48	CP	WH	5'	C5	
		750LF*	40K	OC			CLV60	EC		6'	C6		
		875LF*					CLV96	EM		8'	C8		
		1000LF									M		

†Consult cutsheet run guide for standard configurations

\*750LF and 875LF not DLC with 4', 5' or 6' lengths

OBSCURA	FOSS	FL80	500LF	30K	1C	UNV	LD1	G	CLV24	CSS	PS	4'
			625LF	35K			HS	CLV48	CP	PSM	5'	
			750LF	40K			OC	CLV60	EC	WH	6'	
			875LF					CLV96	EM	WHM	7'	
			1000LF								8'	
											9'	
							10'					
							11'					
							12'					

\*4' 500LF DLC with 40K color temperature only, 5' & 6' 500LF DLC with 35K & 40K color temperatures only.



# DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

## RECESSED LINEAR

Fixture	Luminaire Series	Shielding	Nominal Output	Color Temperature	Circuit	Voltage	Driver	Ceiling Configuration	Factory Options	Finish	Length
SEEM 4 LED RECESSED DRYWALL / HARD CEILING	FSM4L	FL	375LF	30K	1C	UNV	LD1	TF, TFW, XF1, XF2, XFF, XFN, XFW, CXF1, CXF2, CXFF, CXFN, CXFW	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 4-8' and runs comprised of 4-8' units
			625LF	35K							
			875LF	40K							
SEEM 4 LED RECESSED GRID CEILING	FSM4L	FL	375LF	30K	1C	UNV	LD1	G1, T1, G2, T2, G3, G4, T4, G5, T5, T6	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 4-8' and runs comprised of 4-8' units
			625LF	35K							
			875LF	40K							
			1000LF								
SEEM 4 LED ASYMMETRIC ANGLED LENS	FSM4AL	FL	375LF*	30K	1C	UNV	LD1	G1, T1, G2, T2, G3, T3, G5, T5, T6, TF, TFW, XF1, XF2, XFF, XFN, XFW, CXF1, CXF2, CXFF, CXFN, CXFW	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 2-8' and runs comprised of 2-8' units
			625LF	35K							
			875LF	40K							
SEEM 4-LP	FSM4LP	FL	375LF*	30K	1C	UNV	LD1	G1, T1, G2, T2, G3, G4, T4, G5, T5, T6	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 2' and 4' - 8' lengths and runs comprised of 4' - 8' units
		RL	625LF	35K							
			875LF	40K							
			1000LF								

\*375LF 4' length minimum

\*375LF 4' - 8' only.