



DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

RECESSED

Fixture	Luminaire Series	Nominal Size	Shielding	Lumen Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Options	Finish
AERION LED	FARL	24	AC	4000L	30K	1C	120	L11	G1	AR, CP, EM,	WH
			RA*	4000LH	35K		277	LD1	G2	FNY, FW	WHA
			SA*	4500L	40K		UNV	G3			
				4500LH				F			
				5000L							
				5000LH							
				5500L							
				5500LH							
	6000LH							*RA & SA not DLC with 5000L or 5500L			
AMICA 2	FAM2	24	AC	4000L	30K	1C	120	L11	G1	AR, CP, EM,	WH
			RA*	4000LH	35K		277	LD1	G2	FNY, FW	WHA
			SA*	4500L	40K		UNV	G3			
				4500LH				F			
				5000L							
				5000LH							
				5500L							
				5500LH							
	6000LH							*RA & SA not DLC with 5000L or 5500L			
AMICA LED	FAML	24	ACR	4000L	30K	1C	120	L11	G1	AR, CP, EM,	WH
				4000LH	35K		277	LD1	G2	FNY, FW	WHA
				4500L	40K		UNV	G3			
				4500LH				F			
				5000L							
				5000LH							
				5500L							
				5500LH							
	6000LH										



Amica 2 is listed as DLC Premium unless otherwise indicated. Visit designlights.org/QPL for model specifics.



DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

RECESSED continued

Fixture	Luminaire Series	Nominal Size	Shielding	Lumen Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Options	Finish					
EQUATION 2	FEQ2	14	AC	2000L	30K	1C	UNV	LD1	C24	AR	WH					
				2500L	35K			L11	C48	CP						
				3000L	40K				C96	EM						
				3500L					F	FNY1						
				4000L					G	FNY2						
				4500L					ST	FW						
				5000L					SM							
		22	AC	2000	30K	1C	UNV	LD1	L11	C24	AR	WH				
													2500*	35K	C48	CP
													3000*	40K	C96	EM
													2000LH		F	FNY1
													2500LH		G	FNY2
													3000LH		ST	FW
													3500LH		SM	
													4000LH			
													4500LH			
													5000LH			
		*LD1 driver only														
		24	AC	4000L	30K	1C	UNV	LD1	L11	C24	AR	WH				
													4500L	35K	C48	CP
													5000L	40K	C96	EM
													5500L		F	FNY1
													4000LH		G	FNY2
													4500LH		ST	FW
													5000LH		SM	
													5500LH			
													6000LH			
													6500LH			
													7000LH			
													8000LH			
8500LH																
FACETTA	FCT	22	FL	2000L	27K	1C	UNV	L11	F	CP, EM, FNY1, FNY2, FW	WH					
				2500L	30K			LD1	G							
				3000L	35K				ST							
				3500L	40K											
				4000L												
VEER LED	FVRL	24	ACF	4000L	30K	1C	120	L11	F	AR, CP, EM, FNY, FW	WH					
			ACG	4000LH	35K			LD1	G							
			ACR	4500LH	40K				UNV			ST				
				5000LH					SM							
				5500LH												
				6000LH												
ZEPHYR	FZR	22	FL	2000L	27K	1C	UNV	L11	F	CP, EM, FNY1, FNY2, FW	WH					
				2500L	30K			LD1	G							
				3000L	35K				ST							
				3500L	40K											
				4000L												



DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

LINEAR

Fixture	Luminaire Series	Shielding	Nominal Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Factory Options	Finish	Length
SEEM 4 LED SUSPENDED / WALL MOUNT	FSM4LS	FL	375LF	30K	1C	UNV	LD1	C24, C48, C96	EC, EM	TS	Individual units 4-8' and runs comprised of 4-8' units
			625LF	35K			L11			WH	
	FSM4LW			40K				WM			

Fixture	Luminaire Series	Shielding	Nominal Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Suspension & Power Feed	Factory Options	Finish	Length	Run Configuration ¹
NERA	FNRS	FL60	500LF	30K	1C	UNV	LD1	G	CLV24	CSS	PS	4'	C4
		FL70	625LF	35K				HS	CLV48	CP	WH	5'	C5
		750LF*	40K	OC				CLV60	EC		6'	C6	
		875LF*						CLV96	EM		8'	C8	
		1000LF										M	
													¹ Consult cutsheet run guide for standard configurations
													*750LF and 875LF not DLC with 4', 5' or 6' lengths
OBSCURA	FOSS	FL80	500LF	30K	1C	UNV	LD1	G	CLV24	CSS	PS	4*	
			625LF	35K				HS	CLV48	CP	PSM	5*	
			750LF	40K				OC	CLV60	EC	WH	6*	
			875LF						CLV96	EM	WHM	7'	
			1000LF									8'	
												9'	
							10'						
							11'						
							12'						
													*4' 500LF DLC with 40K color temperature only. 5' & 6' 500LF DLC with 35K & 40K color temperatures only.



DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

RECESSED LINEAR

Fixture	Luminaire Series	Shielding	Nominal Output	Color Temperature	Circuit	Voltage	Driver	Ceiling Configuration	Factory Options	Finish	Length
SEEM 4 LED RECESSED DRYWALL / HARD CEILING	FSM4L	FL	375LF	30K	1C	UNV	LD1	TF, TFW, XF1, XF2, XFF, XFN, XFW, CXF1, CXF2, CXFF, CXFN, CXFW	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 4-8' and runs comprised of 4-8' units
			625LF	35K							
				40K							
SEEM 4 LED RECESSED GRID CEILING	FSM4L	FL	375LF	30K	1C	UNV	LD1	G1, T1, G2, T2, G3, G4, T4, G5, T5, T6	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 4-8' and runs comprised of 4-8' units
			625LF	35K							
			875LF	40K							
			1000LF								
SEEM 4 LED ASYMMETRIC ANGLED LENS	FSM4AL	FL	375LF*	30K	1C	UNV	LD1	G1, T1, G2, T2, G3, T3, G5, T5, T6, TF, TFW, XF1, XF2, XFF, XFN, XFW, CXF1, CXF2, CXFF, CXFN, CXFW	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 2-8' and runs comprised of 2-8' units
			625LF	35K							
			875LF	40K							
SEEM 4-LP	FSM4LP	FL	375LF*	30K	1C	UNV	LD1	G1, T1, G2, T2, G3, G4, T4, G5, T5, T6	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 2' and 4' - 8' lengths and runs comprised of 4' - 8' units
		RL	625LF	35K							
			875LF	40K							
			1000LF								

*375LF 4' length minimum

*375LF 4' - 8' only.