



DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

RECESSED

Fixture	Luminaire Series	Nominal Size	Shielding	Lumen Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Options	Finish				
AERION LED	FARL	14	AC	2500L	30K	1C	120	L11	G1	AR, CP, EM,	WH				
			RA*	3000L	35K		277	LD1	G2	FNY, FW	WHA				
			SA*	3500L	40K		UNV	G3							
				4000L	*RA & SA not DLC with 4000L										
		22	AC	2000L	30K	1C	120	L11	G1	AR, CP, EM,	WH				
				2500LH	35K		277	LD1	G2	FNY, FW	WHA				
				3000LH	40K		UNV	G3							
				3500LH											
		24	AC	4000L	30K	1C	120	L11	G1	AR, CP, EM,	WH				
			RA*	4000LH	35K		277	LD1	G2	FNY, FW	WHA				
			SA*	4500L	40K		UNV	G3							
				4500LH											
			5000L												
			5000LH												
			5500L												
	5500LH														
	6000LH	*RA & SA not DLC with 5000L or 5500L													
AMICA 2	FAM2	22	ACR	2500L†	30K	1C	UNV	LD1	G	AR	WH				
				2500LH	35K				F	CP					
				3000L†	40K				SM	EM					
				3000LH					C24	FNY1					
				3500L†					C48	FNY2					
				3500LH					C96	FW					
				4000L†											
				4000LH	†Indicates DLC Standard qualified products										
			24	ACR	4000L				30K	1C	UNV	LD1	G	AR	WH
					4000LH				35K				F	CP	
					4500L				40K				SM	EM	
					4500LH								C24	FNY1	
					5000L								C48	FNY2	
					5000LH								C96	FW	
		5500L													
	5500LH														
AMICA LED	FAML	22	ACR	2000L	30K	1C	120	L11	G1	AR, CP, EM,	WH				
				2500LH	35K		277	LD1	G2	FNY, FW	WHA				
				3000LH	40K		UNV	G3							
				3500LH											
		24	ACR	4000L	30K	1C	120	L11	G1	AR, CP, EM,	WH				
				4000LH	35K		277	LD1	G2	FNY, FW	WHA				
				4500L	40K		UNV	G3							
				4500LH											
		5000L													
		5000LH													
	5500L														
	5500LH														
	6000LH														

Amica 2 versions listed are DLC Premium unless otherwise indicated. Visit designlights.org/QPL for model specifics.



DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

RECESSED continued

Fixture	Luminaire Series	Nominal Size	Shielding	Lumen Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Options	Finish											
EQUATION 2	FEQ2	14	AC	2000L	35K	1C	UNV	LD1	C24	AR	WH											
			MG	2500L	40K			L11	C48	CP												
		22	AC	MG	2000LH	35K	1C	UNV	LD1	C24	AR	WH										
					2500LH	40K					L11		C48	CP								
					3000LH								C96	EM								
					3500LH								F	FNY1								
													G	FNY2								
													ST	FW								
													SM									
					24	AC					MG		4000LH	35K	1C	UNV	LD1	C24	AR	WH		
													4500LH	40K					L11		C48	CP
													5000LH								C96	EM
													5500LH								F	FNY1
													6000LH								G	FNY2
													6500LH								ST	FW
7000LH			SM																			
FACETTA	FCT	22	FL	2000L	27K	1C	UNV	L11	F	CP, EM, FNY1, FNY2, FW	WH											
				2500L	30K			LD1	G													
				3000L	35K				ST													
				3500L	40K																	
				4000L																		
VEER LED	FVRL	24	ACF	4000L	30K	1C	120	L11	F	AR, CP, EM, FNY, FW	WH											
				ACG	4000LH		35K	277	LD1			G										
				ACR	4500LH		40K	UNV	ST													
					5000LH				SM													
					5500LH																	
					6000LH																	
ZEPHYR	FZR	14	FL	2000L	27K	1C	UNV	L11	F	CP, EM, FNY1, FNY2, FW	WH											
					30K			LD1	G													
					35K				ST													
					40K																	
		22	FL	2000L	27K	1C	UNV	L11	F	CP, EM, FNY1, FNY2, FW	WH											
					2500L				30K			LD1	G									
					3000L				35K				ST									
					3500L				40K													
					4000L																	



DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

LINEAR

Fixture	Luminaire Series	Shielding	Nominal Output	Color Temperature	Circuit	Voltage	Driver	Mounting	Factory Options	Finish	Length			
SEEM 4 LED SUSPENDED / WALL MOUNT	FSM4LS	FL	375LF 625LF	30K 35K 40K	1C	UNV	LD1 L11	C24, C48, C96	EC, EM	TS WH	Individual units 4-8' and runs comprised of 4-8' units			
	FSM4LW							WM						
TWELVE LED	FTWLS	AC	750LF	30K*	1C	UNV	LD1	J12	DC, EC, EM	TS	4'			
		MG	875LF	35K				J24		WH	8'			
			1000LF	40K				J48			12' (8' + 4')			
			1125LF					J96			16' (8' + 8')			
			1250LF					S__			20' (8' + 4' + 8') 24' (8' + 8' + 8')			
*30K not DLC with 875LF, 1000LF or 1250LF														
NERA	FNRS	FL60	500LF	30K	1C	UNV	LD1	G, HS, OC	CLV24	CCS, CP, EC, EM	PS WH	4'	C4	
		FL70	625LF	35K					CLV48			5'	C5	
			750LF*	40K						CLV60			6'	C6
			875LF*							CLV96			8'	C8
			1000LF											M
*Consult cutsheet run guide for standard configurations														
*750LF and 875LF not DLC with 4', 5' or 6' lengths														
OBSCURA	FOSS	FL80	500LF	30K	1C	UNV	LD1	G, HS, OC	CLV24	CCS, CP, EC, EM	PS PSM	4**		
			625LF	35K					CLV48			5**		
			750LF	40K						CLV60		WH	6**	
			875LF							CLV96		WHM	7'	
			1000LF										8'	
													9'	
											10'			
											11'			
											12'			
*4' 500LF DLC with 40K color temperature only. 5' & 6' 500LF DLC with 35K & 40K color temperatures only.														



DesignLights Consortium

QUALIFIED LUMINAIRES REFERENCE



FOCAL POINT®

RECESSED LINEAR

Fixture	Luminaire Series	Shielding	Nominal Output	Color Temperature	Circuit	Voltage	Driver	Ceiling Configuration	Factory Options	Finish	Length
SEEM 4 LED RECESSED / WALL TO CEILING	FSM4L	FL	375LF 625LF	30K 35K 40K	1C	UNV	LD1 L11	G1, T1, G2, T2, G3, G4, T4, G5, T5, T6, TF, TFW, XF1, XF2, XFF, XFN, XFW, CXF1, CXF2, CXFF, CXFN, CXFW	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 4-8' and runs comprised of 4-8' units
SEEM 4 LED ASYMMETRIC ANGLED LENS	FSM4AL	FL	375LF* 625LF 875LF	30K 35K 40K	1C	UNV	LD1 L11	G1, T1, G2, T2, G3, T3, G5, T5, T6, TF, TFW, XF1, XF2, XFF, XFN, XFW, CXF1, CXF2, CXFF, CXFN, CXFW	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 2-8' and runs comprised of 2-8' units
SEEM 4-LP	FSM4LP	FL RL	375LF* 625LF 875LF 1000LF	30K 35K 40K	1C	UNV	LD1 L11	G1, T1, G2, T2, G3, G4, T4, G5, T5, T6	CP, EC, EM, FNY1, FNY2, FW	WH	Individual units 2' and 4' - 8' lengths and runs comprised of 4' - 8' units

*375LF 4' length minimum

*375LF 4' - 8' only.