


COMING MAY 2021

ID+ 2.5"

OVERLAP & TRIMLESS LED DOWNLIGHTS



Solite lens



Clear diffuse



Warm diffuse




Black



White




Optional painted
flanges




Wall Wash
companion

DIMENSIONAL DATA



Field adjustability of ceiling thickness from 0.5" - 1.5"
Housing height with DALI, Lutron & LZ1 drivers is 3.0"



FEATURES

Less than 2.64" low profile housing available.

60° and 75° cut-off reflector options available.


25° to 90° beam spreads support accent lighting, task lighting and general illumination

Solite lens with die-cast trim delivers 70° or 90° beam spread options.

Warm Dim: Lighting that enhances spaces with a warm glow, reminiscent of incandescent or halogen light sources.

PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

DISTRIBUTIONS




Photometric performance is measured in accordance with IESNA LM-79.
Visit focalpointlights.com for complete photometric data.

fixture:

project:

HOUSING DETAILS



HOUSING SPECIFICATIONS

Construction

Thermally protected housing for new construction applications. Insulation to be kept 3" away from housing. Type IC inherently protected, suitable for direct contact with insulation. Restrictive airflow per ASTM-E283. Butterfly brackets allow mounting to 1/2" emt. Order bar hangers as an accessory. Die-cast aluminum heat sink designed for maximum thermal dissipation. Die-formed housing and integral junction box with (7) 1/2" pry outs. Accommodates ceiling thicknesses up to 0.5" standard, field adjustable up to 1.5" thickness. For thicker ceiling consult factory. Fixture will not exceed 5 lb.

Electrical

Choice of constant current dimming drivers. Power factor > .9 typical. PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

Emergency

Above ceiling access required, overlap trim only. Emergency output - 7W for 90 minutes. Maximum mounting height: Clear Diffuse & White: 23.2ft. Black & Warm Diffuse: 15.5ft.

Labels

UL and cUL Listed. Suitable for Dry, Damp or Wet Locations, indoor use only. Specify Outdoor rated (OD) for outdoor recessed ceiling applications.

Lumen Maintenance

Reported: L70 at >55,000 hours Calculated: L70 at 204,000 hours
L90 at >55,000 hours L90 at 59,000 hours

Derived from EPA TM-21 calculator. Based on typical conditions, consult factory for additional data.

Reliability

At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.

Warranty

LED System rated for operation in ambient environments up to 25°C. 5-year limited warranty. Fixture with Outdoor rated option must be installed in a covered ceiling and is warrantied for operation in ambient environments between -20°C to +25°C.

TRIM & LED SPECIFICATIONS

LED System

Proprietary array incorporates premium LEDs on a robust platform. May be specified in 2700K, 3000K, 3500K or 4000K, or Warm Dimming (2700K-1800K and 3000K-1800K), CRI>80, >90 or 97. Color accuracy within 2 SDCM (Warm Dimming from 3-5 SDCM). Aluminum heat sink provides appropriate thermal management.

Aesthetics

Die-cast aluminum trims. Overlap trims are self-flanged.

Optics


60-degree or 75-degree cut-off to light source and its image.

Optic	Cut-Off Degree	Trim Type	Distribution Beam Spread Spacing Criteria						
			NFL	FL1	FL2	WFL1	WFL2	VWFL	SWFL
DNS	60°	Overlap	20° 0.36	33° 0.54	42° 0.68	52° 0.80	64° 0.92	-	-
		Trimless	21° 0.38	33° 0.54	43° 0.68	51° 0.78	62° 0.88	-	-
DSS	75°	Overlap	-	-	-	-	-	70° 1.02	81° 1.14
		Trimless	-	-	-	-	-	69° 0.98	89° 1.26

PERFORMANCE TABLE - see page 3.

HOUSING ORDERING		FLC2D
Housing Series	ID+ 2.5" Round	
Trim Type	Round Overlap	RDO
	Round Trimless	RDT
Color Options	Standard White, 80 & 90 CRI	SW
	High 97 CRI	HC
	Warm Dim	WDM
(900L only. UNV, LV & EMR not available.)		
Lumen Output	500 Lumen	500L
(LT1, LD1 & LVN only)		
	700 Lumen	700L
(Not available with LFP, LTE or LH1)		
	900 Lumen	900L
(Not available with LFP or LH1)		
	1100 Lumen	1100L
	1300 Lumen	1300L
	1500 Lumen	1500L
	1700 Lumen	1700L
	1900 Lumen	1900L
(LT1, LD1 & LH1 only)		
Voltage	120/277 Volt	UNV
(IC housing: SW & HC: 1500L max. T & TW housings: SW 1100L max., HC: 900L max.)		
	120V	120
	277V	277
Low Voltage		LV
(IC housing: SW & HC: 1500L max. T & TW housings: SW 1100L max., HC: 900L max.)		
Control System & Dimming Level	0-10V <1% Dimming	LZ1
	0-10V - 1% Dimming	L11
	0-10V - 10% Dimming	LD1
Low Voltage, PoE Compatible		LVN
(No driver. Not available with EMR. LV voltage only.)		
	Forward Phase (120V only)	LFP
	Lutron Hi-Lume EcoSystem (LDE1) -	LH1
	1% Dimming	
	Lutron Hi-Lume - Forward Phase (120V) -	LTE
	1% Dimming	
	DALI <1% Dimming	DZ1
	DALI - 1% Dimming	D11
Housing Type	IC Rated / Airtight	IC
(1500L max.)		
	Thermally Protected, Non-IC	T
	Thermally Protected, Non-IC Wood	TW
(Trimless only. Wood kit required)		
Factory Options	Bar Hangers	BH
	Chicago Plenum	CP
Emergency Battery -Remote test switch		EMR
(Overlap trim & T Housing only. Above ceiling access.)		
	Outdoor Rated	OD
(LD1 driver and T-rated housing only. Not available with CP or EMR. See dimming performance table on page 3.)		
TRIM & LED MODULE		
Aperture	2.5" Round Reflector	LC2
	2.5" Round Airtight Reflector	LC2AT
Trim Type	Round Overlap	RDO
	Round Trimless	RDT
Lumen Output		
Trim & housing output must match. See options above.		
Color Temperature		
(Add 9 for 90 CRI or H for 97 CRI. Leave blank for 80 CRI. Examples: 2700K, 97 CRI = H27K. 2700K, 80 CRI = 27K.)		
	2700K, 80/90/97+ CRI	_27K
	3000K, 80/90/97+ CRI	_30K
	3500K, 80/90/97+ CRI	_35K
	4000K, 80/90/97+ CRI	_40K
	Warm Dim: 2700-1800K, 90+ CRI	92718W
	Warm Dim: 3000-1800K, 90+ CRI	93018W
Optic		
	Short Cone with 60° cut-off	DNS
	Super Short Cone with Solite Lens 75° cut-off	DSS
Distribution		
	Narrow Flood	NFL
	Flood	FL1
	Flood	FL2
	Wide Flood	WFL1
	Wide Flood	WFL2
	Very Wide Flood (DSS only)	VWFL
	Super Wide Flood (DSS only)	SWFL
Finish		
	Clear Diffuse	CD
	Warm Diffuse	WD
	Black	BK
	White	WH
Optional Flange Finish		
(Overlap CD & WD finish only) (For matching finishes leave blank)		
	Black Painted	BP
	White Painted	WP
ACCESSORIES		
	Trimless Wood Ceiling Installation Kit	LC2-WOOD-KIT
(One kit recommended per 10 downlights)		

2.5" ROUND DOWNLIGHT PERFORMANCE TABLE

Lumen Output	Delivered Lumens	System Watts	LPW
500L	513	6	86
700L	756	8.2	92
 900L	880	14.6	60
900L	929	9.9	94
1100L	1139	11.9	96
1300L	1354	16.2	84
1500L	1527	18.1	84
1700L	1746	20.7	84
1900L	1949	23.3	84

Based on Overlap, Short cone, 3500K, 80 CRI, Flood 2, Clear Diffuse. WDM based on 3000 - 1800K, 90 CRI. Delivered lumen output may vary +/- 5%. Actual wattage may vary +/- 5%

OUTDOOR RATED (OD) DRIVER DIMMING PERFORMANCE TABLE

Lumen Output	Minimum Dimming Level
500L	25%
700L	17%
900L	13%
1100L	10%
1300L	10%
1500L	10%
1700L	10%
1900L	10%

2.5" ROUND DOWNLIGHT LUMEN MULTIPLIER TABLE

Color Temperature & CRI

Trim Type	Optic	Color Temperature & CRI		Multiplier
ALL	ALL	2700K	80+ CRI [27K]	0.92
			90+ CRI [927K]	0.79
			97 CRI [H27K]	0.67
		3000K	80+ CRI [30K]	0.98
			90+ CRI [930K]	0.83
			97 CRI [H30K]	0.72
		3500K	80+ CRI [35K]	1.00
			90+ CRI [935K]	0.82
			97 CRI [H35K]	0.73
		4000K	80+ CRI [40K]	1.01
			90+ CRI [940K]	0.84
			97 CRI [H40K]	0.76
		2700-1800K	90+ CRI [92718K]	0.93
		3000-1800K	90+ CRI [93018K]	0.98

Distribution

Trim Type	Optic	Distribution	Multiplier
Round Trimless [RDT]	Short Cone with 60° cut-off [DNS]	Narrow Flood [NFL]	1.05
		Flood 1 [FL1]	0.99
		Flood 2 [FL2]	1.03
		Wide Flood 1 [WFL1]	1.00
		Wide Flood 2 [WFL2]	0.91
		Very Wide Flood [VWFL]	0.85
Round Overlap [RDO]	Super Short Cone with Solite Lens with 75° cut-off [DSS]	Super Wide Flood [SWFL]	0.75
	Short Cone with 60° cut-off [DNS]	Narrow Flood [NFL]	1.05
		Flood 1 [FL1]	0.99
		Flood 2 [FL2]	1.03
	Super Short Cone with Solite Lens with 75° cut-off [DSS]	Wide Flood 1 [WFL1]	1.00
		Wide Flood 2 [WFL2]	0.91
		Very Wide Flood [VWFL]	0.85
		Super Wide Flood [SWFL]	0.75

Color

Trim Type	Optic	Color	Multiplier
ALL	Short Cone with 60° cut-off [DNS]	Clear Diffuse [CD]	1.00
		Warm Diffuse [WD]	0.99
		White [WH]	1.08
		Black [BK]	0.90
	Super Short Cone with Solite Lens with 75° cut-off [DSS]	Clear Diffuse [CD]	1.00
		Warm Diffuse [WD]	0.98
		White [WH]	1.08
		Black [BK]	0.90

How To Use Lumen Multipliers

Formula:
(Lumen Output Value) x
(Color Temperature & CRI) x
(Distribution) x
(Color)

Example:
LC2-RDO-SW-1100L-935K-DNS-FL1-WH

(1100) x (0.83) x (0.99) x (1.08) ≈ 976lm
(estimated delivered lumens)

Multiplier charts are provided to aid with estimation of lumen levels across options. Apply multipliers against ordered Lumen Output to estimate Delivered Lumens. An estimation should make use of all tables through consecutive application of three multipliers. Refer to IES files for most accurate photometric information,