




ID+ 2.5"

LED ADJUSTABLE DOWNLIGHT



DIMENSIONAL DATA



FEATURES

19° beam is ideal for art and object accenting, additional beamreads up to 75° complement any application.

Allows for aiming with locking 35° vertical tilt and 362° rotation of light module.


Overlap and trimless options.

Warm Dim: Lighting that enhances spaces with a warm glow, reminiscent of incandescent or halogen light sources.

PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

Outdoor rating permits use in outdoor covered ceiling applications.


DISTRIBUTIONS



fixture:

project:

HOUSING DETAILS



HOUSING SPECIFICATIONS

LED System

Proprietary LED module with single light emitting source. May be specified in 2700K, 3000K, 3500K or 4000K in CRI>80, CRI>90, or CRI>97. Color accuracy within 2 SDCM. Warm Dim within 3-5 SDCM. Aluminum heat sink provides appropriate thermal management.

Construction

T housing for new construction applications. Insulation to be kept 3" away from housing. Type IC inherently protected, suitable for direct contact with insulation. Butterfly brackets allow mounting to ½" emt. Order bar hangers as an accessory. Cast aluminum heat sink designed for maximum thermal dissipation. Die-formed housing and integral junction box with (7) ½" pry outs. UL & cUL listed for (8) #12 AWG (4 in, 4 out) 90°C conductors and feed through-branch wiring. Accommodates ceiling thicknesses from 0.5"-1.5" standard. For thicker ceiling consult factory. Fixture will not exceed 6lbs.

Adjustment

Manual locking 35° vertical tilt and 362° rotation of light module.

Electrical

Choice of constant current dimming drivers. Power factor > .9 typical. PoE compatible: Integrates with Power over Ethernet lighting systems via standard, low-voltage wires.

Emergency Battery

Emergency output—7W for 90 minutes. Maximum mounting height: Clear Diffuse & White: 17.71ft. Black & Warm Diffuse: 17.15ft. Above ceiling access only.

Labels

UL and cUL listed. Suitable for Dry, Damp or Wet Locations indoor use only. Wet Location Solite lens options only. Specify Outdoor rated (OD) for outdoor recessed ceiling applications.

Lumen Maintenance

Reported: L70 at >55,000 hours Calculated: L70 at 204,000 hours
Reported: L90 at >55,000 hours Calculated: L90 at 59,000 hours
Derived from EPA TM-21 calculator. Based on typical conditions, consult factory for additional data.

Reliability

At Focal Point, our products are designed to stand the test of time. Each luminaire is engineered using superior components, manufactured with the utmost care and rigorously tested. Contact us for reliability data.

Warranty

LED System rated for operation in ambient environments up to 25°C. 5-year limited warranty. Fixture with Outdoor rated option must be installed in a covered ceiling and is warrantied for operation in ambient environments between -40°C to +25°C.

TRIM SPECIFICATIONS

Aesthetics

Parabolic reflector cone ensures glare free optics. Reflector is die-cast aluminum. Torsion springs pull trim tight to the ceiling with no visible fasteners within the trim. Trim is inherently air tight with Solite lens. Trims are self-flanged. Non-painted trim matches reflector finish. White or Black painted flange may also be specified. Spot distribution offered with No lens option for a crisp punch of light. No lens options feature a shroud to conceal internal components and maintain a premium aesthetic while providing a narrow spot distribution.

Optics

TRIM TYPE	Distribution Beam Spread										
	Spacing Criteria										
	SP	NFL1	NFL2	FL1	FL2	FL3	WFL1	WFL2	VWFL	LS1	LS2
RO	19°	21°	27°	31°	35°	45°	54°	64°	75°	22° x 40°	30° x 62°
	0.34	0.36	0.46	0.52	0.58	0.70	0.82	0.94	1.12	0.38 x 0.66	0.50 x 0.90
RT	18°	21°	26°	31°	36°	45°	54°	68°	82°	24° x 32°	28° x 68°
	0.32	0.36	0.44	0.52	0.58	0.72	0.82	0.96	1.16	0.42 x 0.52	0.48 x 0.92

PERFORMANCE CHART

See Page 4

HOUSING ORDERING

Housing Series		FLCS2
ID+ 2.5" Round Housing		FLCS2
Trim Type		
Round Overlap		RO
Round Trimless		RT
Lumen Output		
500 Lumens (LT1, LD1 & LVN only.)		500L
700 Lumens (Not available with LFP, LTE, LH1.)		700L
900 Lumens (Not available with LFP, LTE, LH1.)		900L
1100 Lumens		1100L
1300 Lumens		1300L
1500 Lumens		1500L
(Not available with LFP, LTE or LH1 with IC housing.)		
Color Temperature		
(Add 9 for 90 CRI or H for 97 CRI. Leave blank for 80 CRI.)		
2700K, 80/90/97+ CRI		_27K
3000K, 80/90/97+ CRI		_30K
3500K, 80/90/97+ CRI		_35K
4000K, 80/90/97+ CRI		_40K
Warm Dim: 2700-1800K, 90+ CRI*		92718W
Warm Dim: 3000-1800K, 90+ CRI*		93018W
*(700L Only: EMR not available. UNV & LV not available.)		

Distribution

Spot	SP
Narrow Flood 1	NFL1
Narrow Flood 2	NFL2
Flood 1	FL1
Flood 2	FL2
Flood 3	FL3
Wide Flood 1	WFL 1
Wide Flood 2	WFL 2
Very Wide Flood	VWFL
Linear Spread Lens 1	LS1
Linear Spread Lens 2	LS2

Voltage

UNV 120/277 Volt**	UNV
120 Volt	120
277 Volt	277

Low Voltage**

LV

**(T & TW housings: 900L max.)

Driver

0-10V - 0% Dimming	LZ1
0-10V - 1% Dimming	L11
0-10V - 10% Dimming	LD1
Forward Phase (120V only)	LFP
Low Voltage, PoE Compatible	LVN
(No driver, LV Voltage only. Not available with EM.)	
Lutron Hi-Lume EcoSystem (LDE1) - 1% Dimming	LH1
Lutron Hi-Lume - Forward Phase (120V) - 1% Dimming	LTE
DALI - 0% Dimming	DZ1
DALI - 1% Dimming	D11

Housing Type

IC rated	IC
(Not available with LFP, LTE or LH1 with 1500L.)	
Non-IC	T
Non-IC Wood	TW
(RT only, requires Trimless Wood Kit.)	

Factory Options

Bar Hangers	BH
Chicago Plenum	CP
Emergency Battery with Remote Test Switch	EMR
(T housing only. Not available with Warm Dim. Above ceiling access only.)	
Outdoor Rated	OD
(LD1 driver with T housing only. Solite lens optic only. Not available with CP or EMR. See dimming performance table.)	

TRIM ORDERING

Aperture

2.5" Round Aperture	LCS2
Trim Type	
Round Die-Cast Overlap	RDO
Round Die-Cast Trimless	RDT

Lumen Output

Color Temperature

Distribution

Optic

Solite Lens	SL
(Not available with Spot distribution)	
Spot Optic, no lens, 0°-15° tilt (Spot distribution only)	SP00
Spot Optic, no lens, 15°-35° tilt (Spot distribution only)	SP35

Color

Clear Diffuse	CD
Warm Diffuse	WD
Black	BK
White	WH


Optional Flange Finish

(Overlap CD & WD finish only.) (For matching finishes leave blank.)	
Black Painted	BK
White Painted	WH

ACCESSORIES ORDERING

See Page 3

2.5" ROUND ADJUSTABLE DOWNLIGHT PERFORMANCE TABLE

Lumen Output	Delivered Lumens	System Watts	LPW
500L	500	6.4	79
700L	700	8.6	81
 700L	668	16.6	40
900L	900	10.3	87
1100L	1100	14.7	75
1300L	1300	17.3	75
1500L	1492	20.1	74

Based on SL optic, 3500K, 80CRI, Narrow Flood, Clear Diffuse. Warm Dim based on 3000 - 1800K, 90 CRI. Overlap and trimless offer identical performance. Delivered lumen output may vary +/- 5%. Actual wattage may vary +/- 5%.

2.5" ROUND ADJUSTABLE DOWNLIGHT CBCP CHART

Lumen Output	Distribution	Beamspread	Center Beam Candlepower (CBCP)
1500L	SP	19°	10687
	NFL1	21°	7686
	NFL2	27°	5277
	FL1	31°	3994
	FL2	35°	3288
	FL3	45°	2138
	WFL1	54°	1581
	WFL2	64°	1167
	VWFL	75°	898
	LS1	22° x 40°	4146
	LS2	30° x 62°	2000


Based on Round Overlap trim (RO).

OUTDOOR RATED (OD) DRIVER DIMMING PERFORMANCE TABLE

Lumen Output	Minimum Dimming Level
500L	26%
700L	18%
900L	15%
1100L	11%
1300L	10%
1500L	10%

2.5" ROUND DOWNLIGHT LUMEN MULTIPLIER TABLE

Color Temperature & CRI¹

Color Options	Lumen Output	Color Temperature & CRI	Multiplier
Standard White	All Outputs	2700K, 80+ CRI [27K]	0.92
		2700K, 90+ CRI [927K]	0.79
		2700K, 97+ CRI [9727K]	0.67
		3000K, 80+ CRI [30K]	0.98
		3000K, 90+ CRI [930K]	0.83
		3000K, 97+ CRI [9730K]	0.72
		3500K, 80+ CRI [35K]	1.00
		3500K, 90+ CRI [935K]	0.82
		3500K, 97+ CRI [9735K]	0.73
		4000K, 80+ CRI [40K]	1.01
		4000K, 90+ CRI [940K]	0.84
		4000K, 97+ CRI [9740K]	0.76
 Warm Dim	700L	2700-1800K, 90+ CRI [92718W]	0.93
		3000-1800K, 90+ CRI [93018W]	0.95

Color³

Trim	Color	Multiplier
All	Clear Diffuse [CD]	1.00
	Warm Diffuse [WD]	1.02
	White [WH]	1.05
	Black [BK]	0.99

Distribution²

Trim	Distribution	Multiplier
Overlap & Trimless	Spot [SP]	1.12
	Narrow Flood 1 [NFL1]	0.95
	Narrow Flood 2 [NFL2]	0.99
	Flood 1 [FL1]	0.99
	Flood 2 [FL2]	1.00
	Flood 3 [FL3]	0.95
	Wide Flood 1 [WFL1]	0.94
	Wide Flood 2 [WFL2]	0.90
	Very Wide Flood [VWFL]	0.86
	Linear Spread 1 [LS1]	0.94
	Linear Spread 2 [LS2]	0.88

How To Use Lumen Multipliers

Formula:
(Lumen Output Value) x (Color Temperature & CRI¹) x (Distribution²) x (Color³)

Example:
FLCS2-RO-1500L-935K-FL1-LCS4-RDO-WH
(1500) x (0.82) x (.99) x (1.05) ≈ 1279lm (estimated delivered lumens)

Multiplier charts are provided to aid with estimation of lumen levels across options. Apply multipliers against ordered Lumen Output to estimate Delivered Lumens. An estimation should make use of all tables through consecutive application of three multipliers. Refer to IES files for most accurate photometric information.