



An expression of less is more

With Obscura™, we set out to engineer a luminaire that would push the limits of designing with LEDs, that would exemplify "less is more". Simplicity, efficacy, and beauty were our guiding principles. Its broad batwing distribution with direct task lighting and soft indirect illumination supports the design of open, airy, and minimalistic spaces.









Balancing beauty and functionality

A luminaire with a distinct and streamlined form that supports function; two thin blades of light irradiate the space with powerful yet soft illumination. Coupling the flexibility to customize with its minimalistic design, Obscura delivers a functional architectural statement.

EXTERIOR FINISHES

Palladium Silver






POWER-UP™ TECHNOLOGY


Delivers low-voltage power through





POWERFUL OPTICS

up to 1000lm/ft



80/20 LIGHT DISTRIBUTION

Wide batwing distribution provides comfortable illumination and allows for wide spacing between luminaires.

WIDE SPACING

Broad, even distribution allows for increased spacing of luminaires (up to 16' on center), while maintaining uniformity on the ceiling and work plane.




55' X 55' | 10' CEILING | 24" SUSPENSION | 8' - 1000 LUMENS PER FOOT

14' ROW SPACING						16' ROW SPACING					
2' End-to-End Spacing			4' End-to-End Spacing			2' End-to-End Spacing			4' End-to-End Spacing		
45.3	1.3:1	2.1:1	38.0	1.3:1	2.2:1	38.4	1.4:1	2.7:1	32.2	1.3:1	2.5:1

Key: Average Footcandles (Workplane) | Workplane Uniformity | Ceiling Uniformity LLF: 0.9. Reflectances: 80/50/20. Light levels calculated in AGI-32. Calculations do not include any furniture or partitions.







INTERIOR END CAP FINISHES

Infinity finish reflects illumination, conveying the appearance of continuous void. White finish also available.






3.02"

Actual Size

4.32"

DESIGN FLEXIBILITY

Available in 4' to 12' individual lengths in 1' increments.







LIGHT®



