





EXAMPLE 16' RUN



1-T5/T5HO



1-T8

Nominal run length (ft)	1-T5/T5HO (4.35" overlap)			1-T8 (4.47" overlap)		
	Lamp quantity		Unlit ends (in)	Lamp quantity		Unlit ends (in)
3'	4'	3'		4'		
6		2	0.3'	2		1.8
7		2	0.3'	1	1	1.8
8	3		0.5		2	1.8
9	2	1	0.6	3		4.0
10	1	2	0.6	2	1	4.1
11		3	0.8	4		0.3
12	2	2	0.3'	3	1	0.3
13	5		0.7	2	2	0.3
14	4	1	0.8	1	3	0.3
15	3	2	0.8		4	0.3
16	2	3	1.0	3	2	2.6
17	1	4	1.1	2	3	2.6
18		5	1.1	1	4	2.6
19	6	1	0.8	7		1.0
20	5	2	0.8	6	1	1.0
21	4	3	1.0	5	2	1.1
22	3	4	1.1	4	3	1.1
23	9		1.1	3	4	1.1
24	1	6	0.9	2	5	1.1
25	7	2	1.3	1	6	1.1
26	6	3	1.2		7	1.2
27	5	4	1.3	10		1.8
28	11		1.0	9	1	1.8
29	10	1	1.1	8	2	1.8
30	9	2	1.2	7	3	1.8
31	8	3	1.3	6	4	1.8
32	7	4	1.4	5	5	1.8
33	13		1.2	4	6	1.8
34	12	1	1.2	3	7	1.9
35	11	2	1.3	2	8	1.9
36	10	3	1.4	1	9	1.9
37	9	4	1.5	7	5	0.3
38	15		1.3	6	6	0.3
39	14	1	1.3	5	7	0.4
40	13	2	1.4	4	8	0.4
41	12	3	1.6	3	9	0.4
42	11	4	1.7	2	10	0.4
43	10	5	1.8	1	11	0.4
44	9	6	1.9		12	0.4
45	8	7	1.9	3	10	2.7
46	7	8	2.1	2	11	2.7
47	13	4	1.8	1	12	2.7
48	19		1.5	7	8	1.1

Notes: Lamp overlap is consistent throughout run. Unlit ends vary to provide even light throughout run. Standard configurations listed, consult factory for additional options.